SAFETY DATA SHEET



ARALDITE® 2010-1 HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : ARALDITE® 2010-1 HARDENER

Registration number : Not available. **Product code** : 00055758

Product description :

Other means of : Not available.

identification

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Hardener for adhesive systems

1.3 Details of the supplier of the safety data sheet

Supplier : Huntsman Advanced Materials (Europe)BVBA

Everslaan 45

3078 Everberg / Belgium Tel.: +41 61 299 20 41 Fax: +41 61 299 20 40

e-mail address of person responsible for this SDS

: Global_Product_EHS_AdMat@huntsman.com

E-mail address to request full REACH registration number upon EU member State

Authority request:

REACH_Registration_Nr_AM@huntsman.com

1.4 Emergency telephone number

Supplier

Telephone number : EUROPE: +32 35 75 1234

France ORFILA: +33(0)145425959

ASIA: +65 6336-6011 China: +86 20 39377888 +86 532 83889090 India: + 91 22 42 87 5333 Australia: 1800 786 152 New Zealand: 0800 767 437 USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Ingredients of unknown

toxicity

Ingredients of unknown

ecotoxicity

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

ARALDITE 2010-1 HARDENER 2/19

Date of printing (M)SDS no. : 00055758 : 3 June 2015

Date of issue : 3 June 2015 Version : 5

SECTION 2: Hazards identification

Classification : Xi: R36/38

R43 R52/53

Human health hazards : Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Hazard statements Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention : Wear protective gloves: > 8 hours (breakthrough time): butyl rubber, Ethyl Vinyl

Alcohol Laminate (EVAL). Wear eye or face protection. Wear protective clothing.

Avoid release to the environment.

Response : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF IN EYES:

2/19

Immediately call a POISON CENTER or physician.

Storage : Store locked up.

: Dispose of contents and container in accordance with all local, regional, national **Disposal**

and international regulations.

Hazardous ingredients : triethylene glycol dimercaptan

2,4,6-tris(dimethylaminomethyl)phenol

Dimethyldipropyltriamine

Supplemental label

elements

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

ARALDITE 2010-1 HARDENER 3/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

			Class		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Type
Terphenyl, hydrogenated	CAS: 61788-32-7 EC: 262-967-7	7-13	R53	Aquatic Chronic 4, H413	[1] [2]
2,2'-[1,2-Ethanediylbis (oxy)]bis(ethanethiol)	CAS: 14970-87-7 EC: 239-044-2	3-7	Xn; R20/22 N; R51/53	Acute Tox. 4, H302 Acute Tox. 4, H332 Aquatic Chronic 2, H411	[1]
2,4,6-tris (dimethylaminomethyl) phenol	CAS: 90-72-2 EC: 202-013-9 RRN: 01-2119560597-27	3-7	Xn; R22 C; R34 R52/53	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318	[1]
				Skin Sens. 1B, H317 Aquatic Chronic 3, H412	
N'-(3-Aminopropyl)-N, N-dimethylpropane-1, 3-diamine	CAS: 10563-29-8 EC: 234-148-4	1-3	Xn; R22 C; R35 R43	Acute Tox. 4, H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317	[1]
terphenyl	CAS: 26140-60-3 EC: 247-477-3	0.1-1	N; R50/53	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

<u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under

ARALDITE 2010-1 HARDENER 4/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 4: First aid measures

medical surveillance for 48 hours.

Skin contact

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : Symptomatic treatment and supportive therapy as indicated. Following severe exposure the patient should be kept under medical review for at least 48 hours.

ARALDITE 2010-1 HARDENER 5/19

Date of printing (M)SDS no. : 00055758 : 3 June 2015

Date of issue : 3 June 2015 Version : 5

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides sulfur oxides

halogenated compounds

5.3 Advice for firefighters

Special precautions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

5/19

ARALDITE 2010-1 HARDENER 6/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 6: Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Storage hazard class Huntsman Advanced Materials

: Storage class 8, Corrosive substances

7.3 Specific end use(s)

Recommendations
Industrial sector specific solutions

Not available.Not available.

ARALDITE 2010-1 HARDENER 7/19

Date of printing (M)SDS no. : 00055758 : 3 June 2015

Date of issue : 3 June 2015 Version : 5

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,4,6-tris(dimethylaminomethyl) phenol	DNEL	Long term Inhalation	0.31 mg/m³	Workers	Systemic
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	DNEL	Long term Inhalation	3.7 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	7.5 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	3.7 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	7.5 mg/m³	Workers	Local
	DNEL	Long term Dermal	0.67 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.65 mg/m³	Consumers	Systemic
	DNEL	Long term Inhalation	0.65 mg/m ³	Consumers	Local
	DNEL	Long term Oral	0.2 mg/kg bw/day	Consumers	Systemic

Predicted effect concentrations

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
2,4,6-tris(dimethylaminomethyl) phenol	PNEC	Fresh water	0.084 mg/l	Assessment Factors
·	PNEC	Marine	0.0084 mg/l	Assessment Factors
	PNEC	PNECintermittent	0.84 mg/l	Assessment Factors
	PNEC	Sewage Treatment Plant	0.2 mg/l	Assessment Factors
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	PNEC	Fresh water	9.2 μg/l	Assessment Factors
	PNEC	Marine	0.92 µg/l	Assessment Factors
	PNEC	PNECintermittent	92 μg/l	Assessment Factors
	PNEC	Sewage Treatment Plant	18.1 mg/l	Assessment Factors
	PNEC PNEC PNEC	Fresh water sediment Marine water sediment Soil	0.0336 mg/kg 0.00336 mg/kg 0.00132 mg/kg	Equilibrium Partitioning Equilibrium Partitioning Equilibrium Partitioning

ARALDITE 2010-1 HARDENER 8/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Material of gloves for long term application (BTT>480min):

: butyl rubber, Ethyl Vinyl Alcohol Laminate (EVAL)

Material of gloves for short term/splash application (10min <BTT<480min): : nitrile rubber

(BTT = Break Through Time)

Use gloves approved to relevant standards e.g. EN 374 (Europe), F739 (US). Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers. Additional information can be found for instance at www.gisbau.de.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

ARALDITE 2010-1 HARDENER 9/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Colour : Light yellow Odour : Amine-like. **Odour threshold** : Not available. : Not available. pН : Not available. Melting point/freezing point

Initial boiling point and

boiling range

: >200°C

: Closed cup: 125°C [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)] Flash point

Evaporation rate : Not available. Flammability (solid, gas) : Not available. **Burning time** : Not applicable. **Burning rate** : Not applicable. **Upper/lower flammability or** : Not available.

explosive limits

Vapour pressure : <0.01 kPa [room temperature]

: Not available. Vapour density

Relative density : 1.14

Solubility(ies)

Water solubility : practically insoluble

> 20 deg C

Partition coefficient: n-octanol/ : Not available.

water (LogKow)

Auto-ignition temperature : Not available.

: >200°C **Decomposition temperature Viscosity**

: Dynamic (25°C): 65000 mPa·s Kinematic: Not available. Kinematic (40°C): Not available.

Explosive properties : Not available. Not available. **Oxidising properties**

9.2 Other information

: 1.15 g/cm³ [25°C (77°F)] **Density**

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : strong acids, strong bases, strong oxidising agents

ARALDITE 2010-1 HARDENER 10/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Decomposition products may include the following materials:Carbon oxides, Sulphur oxides, Nitrogen oxides, Burning produces obnoxious and toxic fumes.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Endpoint	Species	Result	Exposure
Terphenyl, hydrogenated	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>10000 mg/kg	-
2,4,6-tris	LD50 Dermal	Rat - Male	>971 mg/kg	-
(dimethylaminomethyl)				
phenol				
	LD50 Oral	Rat - Male,	2169 mg/kg	-
		Female		
N'-(3-Aminopropyl)-N,N-dimethylpropane-1, 3-diamine	LD50 Dermal	Rabbit	1310 mg/kg	-
	LD50 Oral	Rat - Male, Female	1669 mg/kg	-

Conclusion/Summary

: No additional information.

Acute toxicity estimates

Route	ATE value
Inhalation (vapours)	206.4 mg/l

Irritation/Corrosion

Product/ingredient name	Test	Species	Route of exposure	Result
2,4,6-tris (dimethylaminomethyl) phenol	OECD 404 Acute Dermal Irritation/ Corrosion	Rabbit	Skin	Corrosive
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	EPA CFR OECD 404 Acute Dermal Irritation/ Corrosion	Rabbit Rabbit	Eyes Skin	Corrosive Corrosive

Conclusion/Summary

Skin : 2,4,6-tris Corrosive to the skin.

(dimethylaminomethyl)

phenol

N'-(3-Aminopropyl)-N,N- Corrosive to the skin.

dimethylpropane-1,

3-diamine

Eyes : 2,4,6-tris Corrosive to eyes.

(dimethylaminomethyl)

phenol

N'-(3-Aminopropyl)-N,N- Corrosive to eyes.

dimethylpropane-1,

3-diamine

Respiratory: No additional information.

Sensitiser

ARALDITE 2010-1 HARDENER 11/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 11: Toxicological information

Product/ingredient name	Test	Route of exposure	Species	Result
2,4,6-tris (dimethylaminomethyl) phenol	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
N'-(3-Aminopropyl)-N,N- dimethylpropane-1, 3-diamine	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitising

Conclusion/Summary

Skin : No additional information.

Respiratory : No additional information.

Mutagenicity

Product/ingredient name	Test	Result
2,4,6-tris (dimethylaminomethyl) phenol	OECD 471 Bacterial Reverse Mutation Test	Negative
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Negative
	OECD 473 In vitro Mammalian Chromosomal Aberration Test	Negative
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	OECD 471 Bacterial Reverse Mutation Test	Negative
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Negative
	OECD OECD 487- In vitro Mammalian Cell Micronucleus Test	Negative

Conclusion/Summary

: 2,4,6-tris (dimethylaminomethyl) Not mutagenic in a standard battery of genetic toxicological tests.

phenol N'-(3-Aminopropyl)-N,N-

Not mutagenic in a standard battery of genetic

dimethylpropane-1, 3-diamine

toxicological tests.

Carcinogenicity

Product/ingredient name	Test	Species	Exposure	Result	Route of exposure	Target organs
N'-(3-Aminopropyl)-N, N-dimethylpropane-1, 3-diamine	No official guidelines	Mouse	20 months; 3 days per week	Negative	Dermal	-

Conclusion/Summary

: No additional information.

Reproductive toxicity

Product/ingredient name	Test	Species	Result/Result type	Target organs
2,4,6-tris (dimethylaminomethyl) phenol	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral: NOEL	-

Conclusion/Summary

: No additional information.

Teratogenicity

ARALDITE 2010-1 HARDENER 12/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 11: Toxicological information

Product/ingredient name	Test	Species	Result/Result type
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine		Rat - Male, Female	15 mg/kg NOAEL

Conclusion/Summary: No additional information.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Inhalation : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory

system. Exposure to decomposition products may cause a health hazard. Serious

effects may be delayed following exposure.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Eye contact : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation : No specific data.

Ingestion : Adverse symptoms may include the following:

stomach pains

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Delayed and immediate effects and also chronic effects from short and long term exposure

Eye contact: Adverse symptoms may include the following:

pain watering

redness

Short term exposure

Potential immediate

effects

: Not available.

Potential delayed effects: Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects: Not available.

Potential chronic health effects

ARALDITE 2010-1 HARDENER 13/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 11: Toxicological information

Product/ingredient name	Test	Result type		Result	Target organs
2,4,6-tris (dimethylaminomethyl) phenol	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity	NOEL	-	15 mg/kg	brain, liver, spleen
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	Screening Test OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	NOAEL	-	1000 ppm	-
	No official guidelines	NOAEL		>56.3 mg/ kg/d	-
	No official guidelines	NOEC	Vapour	550 mg/m ³	-

Conclusion/Summary: No additional information.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Test	Endpo	int	Exposure	Species	Result	
Terphenyl, hydrogenated	-	Acute	EC50	96 hours	Algae	56	mg/l
	-	Acute	LC50	96 hours	Fish	>100	mg/l
2,4,6-tris (dimethylaminomethyl) phenol	OECD 201 Alga, Growth Inhibition Test	Acute	ErC50 (growth rate)	72 hours Static	Algae	84	mg/l
	Unknown guidelines	Acute	LC50	96 hours Static	Daphnia	718	mg/l
	-	Acute	LC50	96 hours Static	Fish	175	mg/l
	-	Chronic	NOEC	72 hours	Algae	6.25	mg/l
N'-(3-Aminopropyl)-N,N- dimethylpropane-1,3-diamine	DIN DIN 38412 Part 8	Acute	EC50	16 hours Static	Bacteria	181	mg/l
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute	EC50	48 hours Static	Daphnia	9.2	mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute	ErC50 (growth rate)	72 hours Static	Algae	21	mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute	LC50		Fish	>100	mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic	LOAEL		Algae	5.7	mg/l

Conclusion/Summary: terphenyl Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

ARALDITE 2010-1 HARDENER 14/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 12: Ecological information

12.2 Persistence and degradability

Product/ingredient name	Test	Period	Result
2,4,6-tris (dimethylaminomethyl) phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	28 days	4 %
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	ISO ISO 7827, 1984 - Evaluation in an aqueous medium of the ultimate aerobic biodegradability of organic compounds	28 days	100 %

Conclusion/Summary: No additional information.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,4,6-tris (dimethylaminomethyl) phenol	-	-	Not readily
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Terphenyl, hydrogenated	6.5	-	high
2,4,6-tris	0.219	-	low
(dimethylaminomethyl)			
phenol			
N'-(3-Aminopropyl)-N,N-	0.5	-	low
dimethylpropane-1,3-diamine			

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

12.7 Other ecological information

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.

ARALDITE 2010-1 HARDENER 15/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 13: Disposal considerations

European waste catalogue (EWC)

Waste code	Waste designation
07 02 04*	other organic solvents, washing liquids and mother liquors

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	14.1 UN number	14.2 UN proper shipping name
ADR/RID	UN2735	Amines, liquid, corrosive, n.o.s. (2,4,6-Tris(dimethylaminomethyl)phenol, Triethyleneglycol-dimercaptane)
IMDG	UN2735	Amines, liquid, corrosive, n.o.s. (2,4,6-Tris(dimethylaminomethyl)phenol, Triethyleneglycol-dimercaptane). Marine pollutant
IATA	UN2735	Amines, liquid, corrosive, n.o.s. (2,4,6-Tris(dimethylaminomethyl)phenol, Triethyleneglycol-dimercaptane)

	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards	14.6 Special precautions for user	Additional information
ADR/RID	8	III	No.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Hazard identification number 80 Special provisions 274 Tunnel code E
IMDG	8	III	Yes.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. Emergency schedules (EmS) F-A S-B

ARALDITE 2010-1 HARDENER 16/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 14: Transport information

	1- ^	1	T	I —	1
IATA	8	III	No.	Transport within	The
				user's premises:	environmentally
	. /			always transport	hazardous
				in closed	substance mark
				containers that	may appear if
				are upright and	required by other
				secure. Ensure	transportation
				that persons	regulations.
				transporting the	Passenger and
				product know	Cargo Aircraft
				what to do in the	Quantity limitation:
				event of an	5 L
				accident or	Packaging
				spillage.	instructions: 852
				' '	Cargo Aircraft
					Only Quantity
					limitation: 60 L
					Packaging
					instructions: 856
					111011 40110110. 000

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

This product is compliant with the REACH Regulation EC 1907/2006.

Huntsman has pre-registered and is registering all of the substances that it manufactures in or imports into the European Economic Area (EEA) that are subject to Title II of the REACH Regulation.

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Europe inventory : All components are listed or exempted.

Black List Chemicals : Not listed **Priority List Chemicals** : Not listed Integrated pollution : Not listed

prevention and control

list (IPPC) - Air

Integrated pollution : Not listed

prevention and control list (IPPC) - Water **National regulations**

ARALDITE 2010-1 HARDENER 17/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 15: Regulatory information

References : The provision of Safety Data Sheets comes under Regulation 6 of CHIP (CHIP is

the recognised abbreviation for the Chemicals Hazard Information and Packaging

Regulations). This is an addition to the Health and Safety at Work Act 1974.

Australia inventory (AICS) : All components are listed or exempted.

Canada inventory :

China inventory (IECSC) : All components are listed or exempted.

Japan inventory

Korea inventory (KECI) : Listed

New Zealand Inventory of Chemicals (NZIoC)

Philippines inventory

(PICCS)

United States inventory

(TSCA 8b)

: All components are listed or exempted.

Chemical Weapons Convention List Schedule I

Chemicals

: Not listed

Chemical Weapons Convention List Schedule II

Chemicals

: Not listed

Chemical Weapons

Convention List Schedule III

Chemicals

: Not listed

15.2 Chemical Safety

Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr. 1C, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H

statements

: H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

ARALDITE 2010-1 HARDENER 18/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 16: Other information

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302
Acute Tox. 4, H332
Aquatic Acute 1, H400
Aquatic Chronic 1, H410
Aquatic Chronic 2, H411
Aquatic Chronic 3, H412
Aquatic Chronic 4, H413
ACUTE TOXICITY (inhalation) - Category 4
ACUTE AQUATIC HAZARD - Category 1
LONG-TERM AQUATIC HAZARD - Category 2
LONG-TERM AQUATIC HAZARD - Category 3
Aquatic Chronic 4, H413
ACUTE TOXICITY (oral) - Category 4

Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Skin Corr. 1A, H314 SKIN CORROSION/IRRITATION - Category 1A SKIN CORROSION/IRRITATION - Category 1C

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
Skin Sens. 1B, H317 SKIN SENSITIZATION - Category 1B

Full text of abbreviated R phrases

: R22- Harmful if swallowed.

R20/22- Harmful by inhalation and if swallowed.

R34- Causes burns.

R35- Causes severe burns. R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R53- May cause long-term adverse effects in the aquatic environment.

Full text of classifications

[DSD/DPD]

: C - Corrosive Xn - Harmful Xi - Irritant

N - Dangerous for the environment

 (M)SDS no.
 : 00055758

 Date of printing
 : 6/3/2015.

 Date of issue/ Date of
 : 6/3/2015.

revision

Date of previous issue : 6/2/2015.

Version : 5

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

ARALDITE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

ARALDITE 2010-1 HARDENER 19/19

Date of printing : 3 June 2015 (M)SDS no. : 00055758

Date of issue : 3 June 2015 Version : 5

SECTION 16: Other information

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.