

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® METAL G RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesives

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Berlin: 0049 30 19 24 0 & 0049 30 30 68 6 7 11
Bonn: 0049 228 19 27 0 & 0049 228 28 7 3 32 11
Erfurt: 0049 361 73 07 30
Freiburg: 0049 761 16 24 0
Göttingen: 0049 51 19 24 0 & 0049 551 38 31 80
Homburg: 0049 6841 19 24 0
Mainz: 0049 6131 19 24 0 & 0049 6131 23 24 66
München: 0049 89 19 24 0
Nürnberg: 0049 911 39 8 2 45 1
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version 1.1 Revision Date: 08.10.2018 SDS Number: 400001021213 Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard,
Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Warning

Hazard statements

: H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P391 Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2-Propenoic acid, reaction products with dipentaerythritol

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version 1.1 Revision Date: 08.10.2018 SDS Number: 400001021213 Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 25 - < 30
2-Propenoic acid, reaction products with dipentaerythritol	1384855-91-7 - 01-2119980666-22	Eye Irrit. 2; H319 Skin Sens. 1A; H317 Aquatic Chronic 3; H412	>= 10 - < 20
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	9003-36-5 500-006-8 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorhydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Halogenated compounds
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.
- Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.
- Storage class (TRGS 510) : 10, Combustible liquids
- Recommended storage temperature : 2 - 40 °C
- Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

- Specific use(s) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version 1.1 Revision Date: 08.10.2018 SDS Number: 400001021213 Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
barium sulfate	7727-43-7	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
silicon dioxide	7631-86-9	AGW (Inhalable fraction)	4 mg/m ³ (Silica)	DE TRGS 900
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., Colloidal amorphous silica, including pyrogenic silica and in wet processes manufactured silica (precipitated silica, silicagel)., When there is compliance with the OEL and biological tolerance			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version
1.1

Revision Date:
08.10.2018

SDS Number:
400001021213

Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

values, there is no risk of harming the unborn child

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8,33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12,25 mg/m ³
	Workers	Dermal	Systemic effects, Long-term exposure	8,33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12,25 mg/m ³
	Consumers	Dermal	Systemic effects, Short-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	0,75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0,75 mg/kg bw/day
	barium sulfate	Workers	Inhalation	Long-term systemic effects
Workers		Inhalation	Long-term local effects	10 mg/m ³
Consumer use		Inhalation	Long-term systemic effects	10 mg/m ³
Consumer use		Oral	Long-term systemic effects	13000 mg/kg
bis(2-ethylhexyl) adipate		Workers	Inhalation	Long-term systemic effects
	Workers	Inhalation	Systemic effects	17,8 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	4,4 mg/m ³
	Consumers	Inhalation	Systemic effects	4,4 mg/m ³
	Workers	Dermal	Long-term systemic effects	25,5 mg/kg
	Consumers	Dermal	Long-term systemic effects	13 mg/kg
	Consumers	Oral	Long-term systemic effects	1,3 mg/kg
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and	Workers	Dermal	Acute local effects	0,0083 mg/cm ²

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESINVersion
1.1Revision Date:
08.10.2018SDS Number:
400001021213Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

phenol				
	Workers	Dermal	Long-term systemic effects	104,15 mg/kg
	Workers	Inhalation	Long-term systemic effects	29,39 mg/m ³
	Consumers	Dermal	Long-term systemic effects	62,5 mg/kg
	Consumers	Inhalation	Long-term systemic effects	8,7 mg/m ³
	Consumers	Oral	Long-term systemic effects	6,25 mg/kg
silicon dioxide	Workers	Inhalation	Long-term systemic effects	4 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
Remarks:	Assessment Factors	
	Marine water	0,0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0,018 mg/l
	Assessment Factors	
	Fresh water sediment	0,996 mg/kg
	Equilibrium method	
	Marine sediment	0,0996 mg/kg
	Equilibrium method	
	Soil	0,196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
barium sulfate	Fresh water	115 µg/l
	Sewage treatment plant	62,2 mg/l
	Assessment Factors	
	Fresh water sediment	600,4 mg/kg
	Assessment Factors	
	Soil	207,7 mg/kg
	Assessment Factors	
bis(2-ethylhexyl) adipate	Fresh water	0,0032 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version 1.1 Revision Date: 08.10.2018 SDS Number: 400001021213 Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

	Marine water	0,0032 mg/l
	Sewage treatment plant	35 mg/l
Assessment Factors		
	Freshwater - intermittent	0,0032 mg/l
	Fresh water sediment	15,6 mg/kg
Equilibrium method		
	Marine sediment	17 mg/kg
Equilibrium method		
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	Fresh water	0,003 mg/l
Assessment Factors		
	Marine water	0,0003 mg/l
Assessment Factors		
	Intermittent use/release	0,0254 mg/l
Assessment Factors		
	Fresh water sediment	0,294 mg/kg
Equilibrium method		
	Marine sediment	0,0294 mg/kg
Equilibrium method		
	Soil	0,237 mg/kg
Equilibrium method		
	Sewage treatment plant	10 mg/l
Assessment Factors		

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene gloves

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : grey

Odour : No data is available on the product itself.

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 100 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : 1,55 (25 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Density : 1,55 g/cm³ (25 °C)

Solubility(ies)
Water solubility : No data is available on the product itself.
Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds
aluminium oxide

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

2-Propenoic acid, reaction products with dipentaerythritol:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Acute oral toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit
Assessment: Mild skin irritant

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Method: OECD Test Guideline 404
Result: Irritating to skin.

2-Propenoic acid, reaction products with dipentaerythritol:
Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rabbit
Assessment: Mild eye irritant
Method: OECD Test Guideline 405
Result: Irritating to eyes.

2-Propenoic acid, reaction products with dipentaerythritol:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Eye irritation

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:
Species: Rabbit
Method: OECD Test Guideline 405
Result: No eye irritation

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429
Result: Causes sensitisation.

2-Propenoic acid, reaction products with dipentaerythritol:
Test Type: Local lymph node assay (LLNA)
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: The product is a skin sensitiser, sub-category 1A.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:
Exposure routes: Skin
Species: Mouse
Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

: Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

2-Propenoic acid, reaction products with dipentaerythritol:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella tryphimurium and E. coli
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Method: OPPTS 870.5395
Result: negative

2-Propenoic acid, reaction products with dipentaerythritol:

Genotoxicity in vivo : Test Type: Micronucleus test
Test species: Mouse (male and female)
Method: OECD Test Guideline 474
Result: negative

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Genotoxicity in vivo : Cell type: Somatic
Application Route: Oral
Exposure time: 48 h
Dose: 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 2000 mg/kg
Method: OECD Test Guideline 486
Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg
Frequency of Treatment: 7 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 days/week
Method: OECD Test Guideline 453
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

2-Propenoic acid, reaction products with dipentaerythritol:

Species: Rat, male and female

Application Route: inhalation (vapour)

Dose: 0, 12.8, 32 or 80 ppm

12,8 ppm

Method: OECD Test Guideline 451

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: >750 milligram per kilogram
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

60 mg/kg body weight

Method: OECD Test Guideline 414

Result: No teratogenic effects

Species: Rat, female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

180 mg/kg body weight

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Method: OECD Test Guideline 414

Result: No teratogenic effects

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rabbit, female

Application Route: Dermal

General Toxicity Maternal: No observed adverse effect level:

30 mg/kg body weight

Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 3 d

Method: Subchronic toxicity

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Species: Rat, male and female

NOAEL: 250 mg/kg

Application Route: Ingestion

Exposure time: 13 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2,7 mg/l
aquatic invertebrates : Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9,4 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

2-Propenoic acid, reaction products with dipentaerythritol:

Toxicity to fish : LL50 (Cyprinus carpio (Carp)): 13 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 18 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Toxicity to fish : LC50 (Fish): 2,54 mg/l
Exposure time: 96 h
Method: Calculation method

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,55 mg/l
Exposure time: 48 h
Method: Calculation method

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 1,8 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211
Remarks: Information given is based on data obtained from similar substances.

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

2-Propenoic acid, reaction products with dipentaerythritol:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 18 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Biodegradability : Inoculum: activated sludge
Concentration: 3 mg/l
Result: Not biodegradable
Biodegradation: ca. 0 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 150
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 2,7 - 3,6
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol:

Distribution among environmental compartments : Koc: 4460
Method: OECD Test Guideline 121

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 3082
14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

IMDG

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
EmS Code : F-A, S-F
14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version 1.1 Revision Date: 08.10.2018 SDS Number: 400001021213 Date of last issue: 05.10.2018
Date of first issue: 05.10.2018

(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
REACH - List of substances subject to authorisation - Future sunset date : Not applicable

Water contaminating class (Germany) : WGK 2 obviously hazardous to water

TA Luft List (Germany) : Total dust:
Not applicable
: Inorganic substances in powdered form:
Not applicable
: Inorganic substances in vapour or gaseous form:
Not applicable
: Organic Substances:
Not applicable
: Carcinogenic substances:
Not applicable
: Mutagenic:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

Not applicable
: Toxic to reproduction:
Not applicable

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315 : Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® METAL G RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 05.10.2018
1.1	08.10.2018	400001021213	Date of first issue: 05.10.2018

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Irrit. : Eye irritation
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW : Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.