



Dow Automotive

Technical Datasheet

BETACLEAN 4100

Description / Application:

Cleaner with activation properties especially for the pretreatment of plastic materials such as polyamides and blends therefrom.

All Dow Automotive products are primarily developed in co-operation with the automobile manufacturers, according to their needs and their specifications; they are approved for the specific applications as defined by the customer.

The use of the product other than approved application have to be released in written form by the Technical Service of Dow Automotive.

Technical Data:

Basis	Isopropyl alcohol
Colour	colourless, transparent
Density	0.81 g/cm ³ at 23°C
Flashpoint	12 °C
Instruction for use	apply with brush or felt onto the bonding area. No wipe off necessary. Paper-towels or rags are not suitable for the cleaning operation. BC 4100 is not to be used for general cleaning of plastic parts. Obvious contamination should be removed with BC 3350 prior to the BC 4100 application. After activation with BC 4100 it is necessary to apply a compatible plastic primer (e.g. BP 5404). Verify suitability or consult our technical service department.
Processing temperature	10 - 35°C
Shelf life	6 months in unopened container and under appropriate storage conditions. See printed expiry date

Containers

Aluminium containers: 1000 ml

Precaution measures

see material safety data sheet

DOW AUTOMOTIVE Quality Management

Quality is our highest priority. Dow Automotive works with a highly modern Quality Management System which meets all international requirements of QS 9000, VDA-6 and ISO 9001.

The above information implies no liability as to the usage of our products. Since the applications, utilisation and processing of our products are beyond our control, the information given is not intended to replace your own trials with the products to establish their suitability for your particular application.

Our liability is limited to the value of the products supplied by us and used by you.

The information on this data sheet corresponds to the latest findings and supersedes all previous versions.

Dow Automotive AG
CH-8807 Freienbach
Tel. +41(0)55416 81 11
Fax +41(0)55416 82 20

Dow Automotive (Italia) S.r.l.
I-20010 Bareggio (MI)
Tel. +39(0)2 90 36 11 66
Fax +39(0)2 90 27 66 98

Dow Automotive (France) S.A.
F-60130 Saint-Just en chaussee
Tel. +33(0) 3 44 77 61 00
Fax. +33(0) 3 44 77 61 61

Dow Automotive (Deutschland) GmbH
D-35683 Dillenburg
Tel. +49(0)2771 8 71 40
Fax +49(0)2771 87 14 70

Dow Automotive (España) S.A.
E-28816 Camarma de Esteruelas (Madrid)
Tel. +34 (9)1 886 61 43
Fax +34 (9)1 885 75 60

Dow Automotive (UK) Ltd.
GB-Nuneaton-Warwickshire CV10 7QT
Tel. +44 (0) 24 7635 72 00
Fax. +44 (0) 24 7635 72 57