

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ENERGY LINE FAST FILLER RED
Product code : L0EL0076

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels
Substance/Mixture
Chemical nature : Mono compound primer (undercoat)

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA
Via Cecilio 17
22100 Como- CO-
Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.eu
Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: EUH066 Repeated exposure may cause skin dryness or cracking.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

- 67-64-1 acetone

2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Liquid pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
acetone	67-64-1 200-662-2	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 17,5 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

	01-2119471330-49	STOT SE 3; H336 EUH066	
ethyl acetate	141-78-6 205-500-4 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 5 - < 10
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 1 - < 5
isopropanol	67-63-0 200-661-7 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
Reaction mass of 12- hydroxy-N-[2-[(1- oxodecyl)amino]alkyl]oc tadecanamide, 12- hydroxy-N-[2-[(1- oxooctyl)amino]alkyl]oct adecanamide an	126098-16-6 484-050-2 01-0000020228-74	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,25 - < 1
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 01-2119472128-37-0001	Flam. Gas 1; H220 Press. Gas Note U (Table 3.1)	>= 30 - < 50
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 10 - < 12,5
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9		>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person.

If inhaled : Remove to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

advice.

- | | |
|-------------------------|---|
| In case of skin contact | : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place |
| In case of eye contact | : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Seek medical advice.
Put eye-washer on working place
Remove contact lenses. |
| If swallowed | : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Keep at rest. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|-----------------------------|
| Symptoms | : No information available. |
| Risks | : No information available. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--|
| Treatment | : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
Seek medical advice. |
|-----------|--|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|--------------------------------|---|
| Suitable extinguishing media | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray. |
| Unsuitable extinguishing media | : Do NOT use water jet. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--------------------------------------|---|
| Specific hazards during firefighting | : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
|--------------------------------------|---|

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.
Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.
Clean contaminated surface thoroughly.
Dam up.
Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Use only in area provided with appropriate exhaust ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Avoid contact with skin, eyes and clothing.
Smoking, eating and drinking should be prohibited in the application area.
Avoid inhalation of vapour or mist.
For personal protection see section 8.
Thoroughly mix before using
After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Solvent vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Electrical installations / working materials must comply with the technological safety standards.
Keep away from sources of ignition - No smoking.
Store between 5° and 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

German storage class : 2B Aerosol cans and lighters

7.3 Specific end use(s)

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m ³	2000-06-16	2000/39/EC
Further information	:	Indicative			

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000-06-16	2000/39/EC
Further information	:	Indicative			
n-butyl acetate	123-86-4	TWA	50 ppm	2016-03-01	ACGIH
		STEL	150 ppm	2016-03-01	ACGIH
ethyl acetate	141-78-6	TWA	400 ppm	2013-03-01	ACGIH
		TWA	200 ppm 734 mg/m3	2017-01-31	2017/164/EU
		STEL	400 ppm 1.468 mg/m3	2017-01-31	2017/164/EU
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
Talc (Mg3H2(SiO3)4)	14807-96-6	TWA	2 mg/m3		ACGIH
propan-2-ol	67-63-0	TWA	200 ppm	2007-01-01	ACGIH
		STEL	400 ppm	2007-01-01	ACGIH

DNEL

isopropanol

: End Use: Consumers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 319 mg/kg bw/day

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 89 mg/m3

End Use: Consumers
Exposure routes: Oral
Potential health effects: Long-term systemic effects
Value: 26 mg/kg bw/day

End Use: Workers
Exposure routes: Dermal
Potential health effects: Long-term systemic effects
Value: 888 mg/kg bw/day

End Use: Workers
Exposure routes: Inhalation
Potential health effects: Long-term systemic effects
Value: 500 mg/m3

trizinc bis(orthophosphate) : End Use: Workers

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Exposure routes: Inhalation
Potential health effects: Local effects
Value: 5 mg/m³

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Local effects
Value: 83 ppm

End Use: Consumers
Exposure routes: Skin contact
Potential health effects: Local effects
Value: 83 ppm

End Use: Consumers
Exposure routes: Inhalation
Potential health effects: Local effects
Value: 2,5 mg/m³

End Use: Consumers
Exposure routes: Ingestion
Potential health effects: Chronic effects
Value: 0,83 ppm

n-butyl acetate

: End Use: Professional use
Exposure routes: Skin contact
Potential health effects: Local effects
Exposure time: 8 h
Value: 7 ppm

End Use: Professional use
Exposure routes: Inhalation
Potential health effects: Local effects
Value: 48 mg/m³

PNEC
isopropanol

: Fresh water
Value: 140,9 mg/l

Intermittent use/release
Value: 140,9 mg/l

Marine water
Value: 140,9 mg/l

Fresh water sediment
Value: 552 mg/kg

Marine sediment
Value: 552 mg/kg

Soil
Value: 28 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

trizinc bis(orthophosphate) : Sewage treatment plant
Value: 2251 mg/l

: Fresh water
Value: 0,206 mg/l

Marine water
Value: 0,0061 mg/l

Fresh water sediment
Value: 117,8 mg/kg

Marine sediment
Value: 56,5 mg/kg

Soil
Value: 35,6 mg/kg

n-butyl acetate : Water
Value: 0,18 mg/l

Soil
Value: 0,093 mg/kg

8.2 Exposure controls

Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.
Respirator with combination filter for vapour/particulate (EN 141)

Hand protection : Solvent-resistant gloves (butyl-rubber) recommended.
For prolonged or repeated contact use protective gloves.
Protective gloves complying with EN 374.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin should be washed after contact.
Wash your hands and put on barrier creams

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.
Personnel should wear protective clothing.
Flame retardant antistatic protective clothing.
Workers should wear antistatic footwear.

Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Odour : solvent-like

Flash point : < 0 °C

Ignition temperature : not determined

Lower explosion limit : No data available

Upper explosion limit : No data available

Auto-ignition temperature : Not applicable

pH : not determined

Freezing point : Not applicable

Boiling point : not determined

Density : 0,821 g/cm³

Water solubility : not determined

Partition coefficient: n-octanol/water : No data available

Solubility in other solvents : not determined

Relative vapour density : Not applicable

Evaporation rate : not determined

9.2 Other information

Solids by weight : 15,45 %

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Volatile organic compounds : 84,55 %
(VOC) content

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Thermal decomposition : Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l, 4 h, dust/mist, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Components:

acetone :

Acute oral toxicity : LD50: 5.800 mg/kg, Rat

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Acute inhalation toxicity : LC50: 21 ppm, 8 h, Rat(female),

xylene :

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish :
Remarks:
No data is available on the product itself.

Toxicity to fish
acetone : LC50: 4.042 mg/l
Exposure time: 14 d

Species: Fish

isopropanol : LC50: > 100 mg/l
Exposure time: 96 h

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
The following Waste Codes are only suggestions:150110*

SECTION 14: Transport information

14.1 UN number

- ADR : UN 1950
- IMDG : UN 1950
- IATA : UN 1950

14.2 Proper shipping name

- ADR AEROSOLS
- IMDG AEROSOLS
- IATA AEROSOLS

14.3 Transport hazard class(es)

- ADR :
- IMDG : 2.1
- IATA : 2.1

14.4 Packing group

- ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Packing group : Not assigned by regulation

Classification Code : F

IMDG

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D,S-U

IATA

Packing group : II

Labels : 2.1

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA

Environmentally hazardous : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the : Banned and/or restricted

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

market and use of certain
dangerous substances,
preparations and articles
(Annex XVII)

123-86-4	n-butyl acetate
68476-86-8	petroleum gas
108-65-6	2-methoxy-1-methylethyl acetate
64742-95-6	Hydrocarbons, C9, aromatics

MAL-Code-Number : 3-6 (1993)
1.533-m3 air/10 g Product contains low-boiling liquids.
Respiratory protective equipment must be air supplied
respirators.

German storage class : 2B: Aerosol cans and lighters
(TRGS 510)

Risk classification according : Not applicable
to VbF

Water contaminating class : highly water endangering
(Germany) VVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 830/2015.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

List of references

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products(BPR)

This safety datasheet complies with the requirements of Regulation (EC) No. 830/2015.

Key or legend to abbreviations and acronyms used in the safety data sheet

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways;

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road;

ASTM - American Society for the Testing of Materials;

BW - Body weight;

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008;

CMR - Carcinogen, Mutagen or Reproductive Toxicant;

DIN - Standard of the German Institute for Standardization;

ECHA - European Chemicals Agency; EC-Number - European Community number;

ECx - Concentration associated with x% response;

ELx - Loading rate associated with x% response;

EmS - Emergency Schedule;

ErCx - Concentration associated with x% growth rate response; GLP - Good Laboratory Practice;

IATA - International Air Transport Association;

IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk;

IC50 - Half maximal inhibitory concentration;

ICAO - International Civil Aviation Organization;

IMDG - International Maritime Dangerous Goods;

IMO - International Maritime Organization;

ISO - International Organisation for Standardization;

LC50 - Lethal Concentration to 50 % of a test population;

LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose);

MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

NO(A)EC - No Observed (Adverse) Effect Concentration;

NO(A)EL - No Observed (Adverse) Effect Level;

NOELR - No Observable Effect Loading Rate;

OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention;

PBT - Persistent, Bioaccumulative and Toxic substance;

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals;

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail;

SADT - Self-Accelerating Decomposition Temperature;

SDS - Safety Data Sheet;

TRGS - Technical Rule for Hazardous Substances;

UN - United Nations;

vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

ENERGY LINE FAST FILLER RED

Version 1.16

Revision Date 18.04.2019

Print Date 15.07.2020
