

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ENERGY LINE CLEARCOAT  
Product code : L0EL0090

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels  
Substance/Mixture  
Chemical nature : Colourless clearcoat

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : safety@lechler.eu  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)
---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P273 Avoid release to the environment.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

- 78-93-3 butanone

### Additional Labelling:

EUH208 Contains: Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate May produce an allergic reaction.

## 2.3 Other hazards

None known.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Liquid solution

#### Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No	Concentration [%]
---------------	-------------------	---------------------------------------	----------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

	Registration number	1272/2008)	
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 10 - < 20
butanone	78-93-3 201-159-0 01-2119457290-43	EUH066 Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 10 - < 20
Hydrocarbons, C9, aromatics	64742-95-6 918-668-5 01-2119455851-35-0006	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 Note P	>= 2,5 - < 10
butan-1-ol	71-36-3 200-751-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 3
Reaction mass of Bis(1,2,2,6,6- pentamethyl-4- piperidyl) sebacate and Methyl 1,2,2,6,6- pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40-0000	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=1) (Chronic M=1)	>= 0,025 - < 0,1
reaction mass of α-3- (3-(2H-benzotriazol-2- yl)-5-tert-butyl-4- hydroxyphenyl)propiony l-ω-hydroxypoly (oxyethylene) and α-3- (3-(2H-benzotriazol-2- yl)-5-tert-butyl-4- hydroxyphenyl)propiony l-ω-3-(3-(2H- benzotriazol-2-yl)-5- tert-butyl-4- hydroxyphenyl) propionyloxypoly(oxyet hylene)	104810-47-1 400-830-7 01-0000015075-76-0017	Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 0,025 - < 0,1
Substances with a workplace exposure limit :			
dimethyl etherdimethyl ether	115-10-6 204-065-8 01-2119472128-37-0001	Flam. Gas 1; H220 Press. Gas Note U (Table 3)	>= 30 - < 50

For the full text of the H-Statements mentioned in this Section, see Section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                         |   |   |
|-------------------------|---|---|
| General advice          | : | When symptoms persist or in all cases of doubt seek medical advice.<br>Never give anything by mouth to an unconscious person.   |
| If inhaled              | : | Remove to fresh air.<br>Keep patient warm and at rest.<br>If breathing is irregular or stopped, administer artificial respiration.<br>If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : | Take off all contaminated clothing immediately.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Do NOT use solvents or thinners.<br>Put shower on working place           |
| In case of eye contact  | : | Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.<br>Seek medical advice.<br>Put eye-washer on working place<br>Remove contact lenses.                       |
| If swallowed            | : | If accidentally swallowed obtain immediate medical attention.<br>Do NOT induce vomiting.<br>Keep at rest.   |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |                           |
|----------|---|---------------------------|
| Symptoms | : | No information available. |
| Risks    | : | No information available. |

#### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |   |  |
|-----------|---|--|
| Treatment | : | The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.<br>Seek medical advice. |
|-----------|---|--|

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- |                                |   |   |
|--------------------------------|---|---|
| Suitable extinguishing media   | : | Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.<br>Keep containers and surroundings cool with water spray. |
| Unsuitable extinguishing media | : | Do NOT use water jet.   |

#### 5.2 Special hazards arising from the substance or mixture

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).  
  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container
- Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.
- German storage class : 2B Aerosol cans and lighters

### 7.3 Specific end use(s)

- : This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

DNEL

xylene

: End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 65,3 mg/m<sup>3</sup>

End Use: Consumers  
Exposure routes: Oral  
Potential health effects: Long-term systemic effects  
Value: 12,5 mg/kg

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Short-term local effects  
Value: 442 mg/kg

End Use: Workers  
Exposure routes: Dermal  
Potential health effects: Long-term systemic effects  
Value: 212 mg/kg

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 221 mg/m<sup>3</sup>

Hydrocarbons, C9, aromatics

: End Use: Consumers  
Exposure routes: Oral  
Potential health effects: Long-term systemic effects  
Value: 11 mg/kg

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 32 mg/m<sup>3</sup>

End Use: Consumers  
Exposure routes: Dermal  
Potential health effects: Long-term systemic effects  
Value: 11 mg/kg

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 150 mg/m<sup>3</sup>

End Use: Workers  
Exposure routes: Dermal

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

	Potential health effects: Long-term systemic effects Value: 25 mg/kg
butan-1-ol	: End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 55 mg/m3  End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 3125 mg/kg  End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 310 mg/m3
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly (oxyethylene) and $\alpha$ -3-(3-(2H-	: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 0,35 mg/m3  End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0,5 mg/kg  End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 0,085 mg/m3  End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 0,25 mg/kg  End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 0,025 mg/kg
PNEC xylene	: Fresh water Value: 0,32 mg/l  Intermittent use/release Value: 0,32 mg/l  Marine water Value: 0,32 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

	Fresh water sediment Value: 12,46 mg/kg
	Marine sediment Value: 12,46 mg/kg
	Soil Value: 2,31 mg/kg
	Sewage treatment plant Value: 6,58 mg/l
butan-1-ol	: Fresh water Value: 0,08 mg/l
	Intermittent use/release Value: 2,25 mg/l
	Marine water Value: 0,008 mg/l
	Fresh water sediment Value: 0,0324 mg/kg
	Marine sediment Value: 0,032 mg/kg
	Soil Value: 0,01 mg/kg
	Sewage treatment plant Value: 2476 mg/l
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-	: Fresh water Value: 0,0023 mg/l
	Marine water Value: 0,00023 mg/l
	Intermittent use/release Value: 0,028 mg/l
	Sewage treatment plant Value: 10 mg/l
	Fresh water sediment Value: 3,06 mg/kg
	Marine sediment Value: 0,306 mg/kg
	Soil

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

Value: 2 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141)
- Hand protection : Solvent-resistant gloves (butyl-rubber)  
For prolonged or repeated contact use protective gloves.  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing.  
Flame retardant antistatic protective clothing.  
Workers should wear antistatic footwear.

#### Environmental exposure controls

- General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : aerosol

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

Odour	: solvent-like
Flash point	: < 0 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
pH	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 0,7789 g/cm <sup>3</sup>
Water solubility	: not determined
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: not determined
Relative vapour density	: Not applicable
Evaporation rate	: not determined

### 9.2 Other information

Solids by weight	: 9,27 %
Volatile organic compounds (VOC) content	: 90,73 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	: No dangerous reaction known under conditions of normal use.
---------------------	---

### 10.4 Conditions to avoid

Conditions to avoid	: Our products were manufactured in compliance with safety
---------------------	--

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

standards to avoid decomposition and degrading under the defined conditions.

Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : Not applicable

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Product

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l, 4 h, dust/mist, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

#### Components:

##### **Hydrocarbons, C<sub>9</sub>, aromatics :**

Acute oral toxicity : LD<sub>50</sub>: 3.592 mg/kg, Rat, OECD Test Guideline 401

Acute dermal toxicity : LD<sub>50</sub>: > 3.160 mg/kg, Rabbit, OECD Test Guideline 402

##### **Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate :**

Acute oral toxicity : LD<sub>50</sub>: 3.230 mg/kg, Rat

##### **reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly (oxyethylene) and $\alpha$ -3-(3-(2H-**

Acute oral toxicity : LD<sub>50</sub>: > 5.000 mg/kg, Rat, OECD Test Guideline 401

Acute inhalation toxicity : LC<sub>50</sub>: 5,8 mg/l, 4 h, Rat, OECD Test Guideline 403

Acute dermal toxicity : LD<sub>50</sub>: > 2.000 mg/kg, OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxicity to fish

:

Remarks:

No data is available on the product itself.

Toxicity to fish

Hydrocarbons, C9, aromatics

:

LC50: 9,2 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Reaction mass of

Bis(1,2,2,6,6-pentamethyl-4-

piperidyl) sebacate and

Methyl 1,2,2,6,6-

pentamethyl-4-piperidyl

sebacate

:

LC50: 0,97 mg/l

Exposure time: 96 h

Species: Lepomis macrochirus (Bluegill sunfish)

Method: OECD Test Guideline 203

LC50: 7,9 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 203

LC50: 0,9 mg/l

Exposure time: 96 h

Species: Brachydanio rerio (zebrafish)

semi-static test Method: OECD Test Guideline 203

reaction mass of  $\alpha$ -3-(3-(2H-

benzotriazol- 2-yl)- 5-tert-

butyl-4-

hydroxyphenyl)propionyl- $\omega$ -

hydroxypoly (oxyethylene)

and  $\alpha$ -3- (3-(2H-

Reaction mass of

Bis(1,2,2,6,6-pentamethyl-4-

piperidyl) sebacate and

Methyl 1,2,2,6,6-

pentamethyl-4-piperidyl

sebacate

:

LC50: 2,8 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

static test Method: OECD Test Guideline 203

: 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Reaction mass of

Bis(1,2,2,6,6-pentamethyl-4-

piperidyl) sebacate and

Methyl 1,2,2,6,6-

pentamethyl-4-piperidyl

sebacate

:

NOEC: 1 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Method: OECD Test Guideline 211

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions: 150110\*

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1950

IMDG : UN 1950

IATA : UN 1950

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

---

### 14.2 Proper shipping name

**ADR** AEROSOLS

**IMDG** AEROSOLS

**IATA** AEROSOLS

### 14.3 Transport hazard class(es)

**ADR** :

**IMDG** : 2.1

**IATA** : 2.1

### 14.4 Packing group

#### **ADR**

Packing group : Not assigned by regulation

Classification Code : F

#### **IMDG**

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D,S-U

#### **IATA**

Packing group : II

Labels : 2.1

### 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : no

#### **IMDG**

Marine pollutant : no

#### **IATA**

Environmentally hazardous : no

### 14.6 Special precautions for user

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

28553-12-0	di-"isononyl" phthalate
------------	-------------------------

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

MAL-Code-Number : 4-3 (1993)  
2.024-m3 air/10 g Product contains low-boiling liquids. Respiratory protective equipment must be air supplied respirators.

Storage class (TRGS 510) : 2B: Aerosol cans and lighters

Risk classification according to VbF : Not applicable

Water contaminating class (Germany) : highly hazardous to water

Ordinance on facilities for handling substances that are hazardous to water (AwSV)  
Classification according to AwSV, Annex 1 (5.2)



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### 15.2 Chemical safety assessment

No data is available on the product itself.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### List of references

Regulation of the European Parliament and Council Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures (CLP)

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

### Key or legend to abbreviations and acronyms used in the safety data sheet

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## ENERGY LINE CLEARCOAT

Version 1.19

Revision Date 24.02.2020

Print Date 15.07.2020

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.