according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	HYDROFAN SUNSET ORANGE MET.
Product code	:	LNHF0320

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	:	Paints, varnishes and enamels
Substance/Mixture		
Chemical nature	:	Mono compound enamel - finish coat

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299 This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

2.3 Other hazards

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

Print Date 04.02.2019

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Water pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
2-butoxyethanol	111-76-2 203-905-0 01-2119475108-36	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 5 - < 10
isopropanol	67-63-0 200-661-7 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 1 - < 5
Substances with a work	place exposure limit :		
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	Flam. Sol. 1; H228 Note T	>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	 When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
If inhaled	 Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	 Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Put shower on working place

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

In case of eye contact			
		Irrigate copiously with clean, fresh wat minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses.	er for at least 10
If swallowed	:	: If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.	
2 Most important symptoms and o	effe	cts, both acute and delayed	
Symptoms	:	No information available.	
Risks	:	No information available.	
3 Indication of any immediate me	edica	I attention and special treatment needed	l
Treatment	:	: The first aid procedure should be established in consultation with the doctor responsible for industrial medicine. Seek medical advice.	
1 Extinguishing media Suitable extinguishing media	:	Use water spray, alcohol-resistant foar carbon dioxide.	n, dry chemical or
		Keep containers and surroundings coo	l with water spray.
Unsuitable extinguishing media	:	Do NOT use water jet.	
2 Special hazards arising from	the	substance or mixture	
Specific hazards during firefighting	:	As the product contains combustible o will produce dense black smoke contait products of combustion (see section 1) Exposure to decomposition products in health. Cool closed containers exposed to fire Collect contaminated fire extinguishing must not be discharged into drains. Fire residues and contaminated fire ex be disposed of in accordance with local	ining hazardous 0). nay be a hazard to with water spray. y water separately. This tinguishing water must
		•	
3 Advice for firefighters			

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

Print Date 04.02.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ventilate the area. Refer to protective measures listed in sections 7 and 8. Material can create slippery conditions.	Personal precautions	Refer to protective measures listed in sections 7 and 8.
---	----------------------	--

6.2 Environmental precautions

Environmental precautions	 Try to prevent the material from entering drains or water courses.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	Clean with detergents. Avoid solvents.	
	Contain spillage, and then collect with non-combustible	
	absorbent material, (e.g. sand, earth, diatomaceous earth,	
	vermiculite) and place in container for disposal according to	
	local / national regulations (see section 13).	

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposure limits (see section 8).
	Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing.
	Smoking, eating and drinking should be prohibited in the
	application area.
	Avoid inhalation of vapour or mist.
	For personal protection see section 8.
	Thoroughly mix before using
	After using, store in a well-sealed container

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	: Observe label precautions.
areas and containers	Containers which are opened must be carefully resealed and
	kept upright to prevent leakage.
	Store in accordance with the particular national regulations.
	Store between 5° an 35°C in a dry, well ventilated place away
	from source of heat, ignition and direct sunlight.

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4	Revision Date 10.09.2018	Print Date 04.02.2019
	No smoking. Electrical installations / working materials must comply with the technological safety standards.	
Advice on common storage	: Keep away from oxidizing agents and materials.	strongly acid or alkaline
7.3 Specific end use(s)		
	: This information is not available.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Ethylene Glycol Monobutyl Ether	111-76-2	TWA	20 ppm 98 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Ident	ifies the poss	ibility of significant upta	ake through the skinIndic	ative
		STEL	50 ppm 246 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Identifies the poss		ibility of significant upta	ake through the skinIndic	ative
aluminium (Stabilized powder)	7429-90-5	TWA	1 mg/m3	2013-03-01	US OEL
Further information	: Aluminium	1		•	
propan-2-ol	67-63-0	TWA	200 ppm	2007-01-01	US OEL
		STEL	400 ppm	2007-01-01	US OEL

DNEL isopropanol

: End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 319 mg/kg bw/day

End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 89 mg/m3

End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects 5 / 12

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4	Revision Date 10.09.2018	Print Date 04.02.2019
	Value: 26 mg/kg bw/day	
	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic ef Value: 888 mg/kg bw/day	fects
	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic ef Value: 500 mg/m3	fects
PNEC isopropanol	: Fresh water Value: 140,9 mg/l	
	Intermittent use/release Value: 140,9 mg/l	
	Marine water Value: 140,9 mg/l	
	Fresh water sediment Value: 552 mg/kg	
	Marine sediment Value: 552 mg/kg	
	Soil Value: 28 mg/kg	
	Sewage treatment plant Value: 2251 mg/l	
8.2 Exposure controls		
Personal protective equipment		
Respiratory protection	: Apply technical measures to comply with the exposure limits. This should be achieved by a good general practically feasible- by the use of a local ex If the occupational exposure limits cannot be exceptional cases suitable respiratory equip worn only for a short period of time. Respirator with combination filter for vapou 141)	extraction and -if haust ventilation. be met, in pment should be
Hand protection	: Latex gloves For prolonged or repeated contact use prot Protective gloves complying with EN 374.	ective gloves.

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4		Revision Date 10.09.2018	Print Date 04.02.2019
		Please observe the instructions regard breakthrough time which are provided gloves. Also take into consideration the conditions under which the product is u danger of cuts, abrasion, and the conta If used in solution, or mixed with other conditions which differ from EN 374, co the CE approved gloves. Barrier creams may help to protect the they should however not be applied on occurred. Skin should be washed after contact. Wash your hands and put on barrier cr	by the supplier of the e specific local used, such as the act time. substances, and under ontact the supplier of e exposed areas of skin, ace exposure has
Eye protection	:	Chemical resistant goggles must be we Ensure that eyewash stations and safe the workstation location.	
Skin and body protection	:	Skin should be washed after contact. Wear suitable protective clothing.	
Environmental exposure cont	rols		
General advice	:	Try to prevent the material from enterir courses. If the product contaminates rivers and respective authorities.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Odour	:	solvent-like
Flash point	:	> 63 - 100 °C
Ignition temperature	:	not determined
Lower explosion limit	:	No data available
Upper explosion limit	:	No data available
Auto-ignition temperature	:	Not applicable
рН	:	not determined
Freezing point	:	Not applicable
Boiling point	:	not determined

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4	Revision Date 10.09.2018	Print Date 04.02.2019
Vapour pressure	: 1 hPa at 50 °C	
Density	: 1,025 g/cm3	
Water solubility	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Solubility in other solvents	: not determined	
Flow time	: 65 s 6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: Not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 17,73 %	
Volatile organic compounds	: 9,93 %	
(VOC) content Water content	: 72,32 %	
SECTION 10: Stability and re	eactivity	
10.1 Reactivity		
None reasonably foreseeable	2.	
10.2 Chemical stability	-	

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No dangerous reaction known under conditions of normal use.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	 Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
---------------------	--

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing	agents, strongly alkaline and
---	-------------------------------

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4		Revision Date 10.09.2018	Print Date 04.02.2019
	strongly acid materials in order to avoid exothermic reaction		oid exothermic reactions.
10.6 Hazardous decomposition	prod	ucts	
Hazardous decomposition products: Carbon dioxide (CO2), carbon monoxide (CO), oxic nitrogen (NOx), dense black smoke.		xide (CO), oxides of	
Thermal decomposition	: Not applicable		
SECTION 11: Toxicological i	nfor	mation	
11.1 Information on toxicological e	effect	S	
Product			
Acute oral toxicity	: Acute toxicity estimate: > 2.000 mg/kg, Calculation method		mg/kg, Calculation
Acute inhalation toxicity	: Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method		h, vapour, Calculation
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/k	kg, Calculation method
Skin corrosion/irritation	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccatio the skin., The product may be absorbed through the skin.		esulting in desiccation of
		The concentration of each substance in assessing the toxicological effects preparation.	
<u>Components:</u> 2-butoxyethanol :			
Acute oral toxicity	:	Acute toxicity estimate: 500 mg/ toxicity point estimate	/kg, Converted acute
Acute dermal toxicity	:	Acute toxicity estimate: 1.100 mg/kg. point estimate	, Converted acute toxicity

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

Remarks: No data is available on the product itself.

Toxicity	to	fish
isopropa	ano	ol

: LC50: > 100 mg/l Exposure time: 96 h

:

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

Print Date 04.02.2019

12.2 Persistence and degradability		
Biodegradability	:	No data available
12.3 Bioaccumulative potential		
Bioaccumulation	:	No data available
12.4 Mobility in soil		
Mobility	:	No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	:	There is no data available for this product.
information		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions:150110*

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 Proper shipping name

ADR

Not dangerous goods

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

Print Date 04.02.2019

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.6 Special precautions for user

Remarks

: Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain	: Banned and/or restricted

according to Regulation (EC) No. 830/2015

HYDROFAN SUNSET ORANGE MET.

Version 1.4

Revision Date 10.09.2018

Print Date 04.02.2019

dangerous substances, preparations and articles (Annex XVII)

	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
MAL-Code-Number	: 1-3 (1993) 266-m3 air/10 g
Risk classification according to VbF	: Flash Point > 55 °C up to 100 °C, at 15 °C not miscible with water
Water contaminating class (Germany)	: slightly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.