




HF850 – HYDROFAN FLOCK ADDITIVE



1000 ml +
3-4 g

DESCRIPTION

Coagulating powdered additive.

USE

It permits to split solid residues of products you can find inside water you use for washing equipments or in tins or equipments you use for the application of water based products.

For Car Refinishing, it is suggested for the recycling of water used for washing equipments. For Industry, it is suggested for the depuration of residues in paint boxes.

CHARACTERISTICS

- Very efficacious
- It permits to save time for waste disposal

USE

Collect in a container all the residues of equipments washings, then add on the surface a shower of 3-4 g of HF850 HYDROFAN FLOCK ADDITIVE for each litre of water, then mix and shake for some minutes. Leave it for all the night. The day after water will be clear with some residues on the bottom of the container.

If water will not be clear, due to high concentration of product, add again on the surface a shower of 3-4 g of HF850 HYDROFAN FLOCK ADDITIVE.

Water separated from coagulate residues (by filtering or by surfacing) can be used again for washing equipments.

Wastes have to be eliminated in respect of local laws.

RELATED PRODUCTS

- HYDROFAN BASECOAT
- HS611 HYDROFAN 1K SEALER LIGHT GREY
- HS626 HYDROFAN 2K HB SURFACER LIGHT GREY
- HF950 HYDROFAN CLEARCOAT

SPECIAL NOTE

The product is hygroscopic, seal hermetically the can after use.

TECHNICAL DATA SHEET N° 0472-GB
UPDATED 03/2016

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.