according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	TB LECHSYS BRILLIANT RED
Product code	:	L0290046

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Skin irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Central nervous system Chronic aquatic toxicity, Category 3 H226: Flammable liquid and vapour. H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18	Revision Date	20.12.2017	Print Date 30.03.2020
Hazard pictograms		!	
Signal word	: Warning		
Hazard statements	: H226 H315 H336 H412	Flammable liquid and v Causes skin irritation. May cause drowsiness Harmful to aquatic life v effects.	or dizziness.
Precautionary statements	: Prevention: P210	Keep away from heat, I open flames and other smoking.	
	P261 P273	Avoid breathing dust/ fu vapours/ spray. Avoid release to the en	-
	Response: P301 + P310	IF SWALLOWED: Imm POISON CENTER/doc	ediately call a
	P331 P370 + P378	Do NOT induce vomitin In case of fire: Use dry or alcohol-resistant foar	sand, dry chemical

Hazardous components which must be listed on the label:

• 64742-95-6 Hydrocarbons, C9, aromatics

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Fluid pigmented dispersion

Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
Hydrocarbons, C9,	64742-95-6	Flam. Liq. 3; H226	>= 17,5 - < 20

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020

aromatics	918-668-5 01-2119455851-35-0006	STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 Note P	
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 17,5 - < 20
Substances with a work	place exposure limit :		
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt se advice. Never give anything by mouth to an unconscious p	
If inhaled	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artif respiration. If unconscious, place in recovery position and see advice.	
In case of skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use i skin cleanser. Do NOT use solvents or thinners. Put shower on working place	recognized
In case of eye contact	Irrigate copiously with clean, fresh water for at leas minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses.	st 10
If swallowed	If accidentally swallowed obtain immediate medica Do NOT induce vomiting. Keep at rest.	I attention.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No information available.
----------	-----------------------------

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18	Revision Date 20.12.2017	Print Date 30.03.2020
Risks	: No information available.	
4.3 Indication of any immediate me	dical attention and special treatment neede	d
Treatment	: The first aid procedure should be esta with the doctor responsible for industr Seek medical advice.	
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use water spray, alcohol-resistant foa carbon dioxide. Keep containers and surroundings co	
Unsuitable extinguishing media	: Do NOT use water jet.	
5.2 Special hazards arising from	the substance or mixture	
Specific hazards during firefighting	 As the product contains combustible of will produce dense black smoke conta products of combustion (see section 7 Exposure to decomposition products of health. Cool closed containers exposed to fire Collect contaminated fire extinguishin must not be discharged into drains. Fire residues and contaminated fire ex- be disposed of in accordance with loc 	aining hazardous 10). may be a hazard to e with water spray. g water separately. This xtinguishing water must
5.3 Advice for firefighters		
Special protective equipment for firefighters	: Wear self-contained breathing appara necessary.	tus for firefighting if
SECTION 6: Accidental releas	se measures	
6.1 Personal precautions, protective	equipment and emergency procedures	
Personal precautions	: Solvent vapours are heavier than air a	and may spread along

Personal precautions	 Solvent vapours are heavier than air and may spread along floors. Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ventilate the area.
----------------------	--

6.2 Environmental precautions

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18	Revision Date 20.12.2017	Print Date 30.03.2020
Environmental precautions	 Try to prevent the material from entering d courses. If the product contaminates rivers and lake respective authorities. 	
6.3 Methods and materials for cont	ainment and cleaning up	
Methods for cleaning up	 Clean with detergents. Avoid solvents. Contain and collect spillages with non-commaterials, e.g. sand, earth, vermiculite, dia and place in a suitable container. The conshould be cleaned up immediately with a sidecontaminant. One possible (flammable) comprises water (45 parts by volume)/ethat (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A malternative is sodium carbonate (5 parts)/w Pick up and transfer to properly labelled concent contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and hazardous waste. 	atomaceous earth itaminated area suitable) decontaminant anol or isopropanol non-flammable vater (95 parts).

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8. Thoroughly mix before using After using, store in a well-sealed container
Advice on protection against fire and explosion	 Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020

No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	 Observe label precautions. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Electrical installations / working materials must comply with the technological safety standards. Keep away from sources of ignition - No smoking. Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight. Store in accordance with the particular national regulations.
Advice on common storage	: Keep away from oxidizing agents and strongly acid or alkaline materials.
7.3 Specific end use(s)	

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
xylenes	1330-20-7	TWA	50 ppm 221 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Ident	ifies the poss	ibility of significant upta	ake through the skinIndic	ative
		STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	: skin: Ident	ifies the poss	ibility of significant upta	ake through the skinIndic	ative
n-butyl acetate	123-86-4	TWA	150 ppm 713 mg/m3	2007-01-01	ACGIH
	STEL		200 ppm 950 mg/m3	2007-01-01	ACGIH

DNEL n-butyl acetate

 End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h

6 / 14

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED Version 2.18 Revision Date 20.12.2017 Print Date 30.03.2020 Value: 7 ppm End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3 PNEC n-butyl acetate Water Value: 0,18 mg/l Soil Value: 0,093 mg/kg 8.2 Exposure controls **Personal protective equipment** : Apply technical measures to comply with the occupational Respiratory protection exposure limits. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time. Respirator with combination filter for vapour/particulate (EN 141) Hand protection Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Wash your hands and put on barrier creams Chemical resistant goggles must be worn. Eye protection Skin and body protection Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020

Environmental exposure controls

General advice	: Try to prevent the material from entering drains or water courses.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
рН	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,0265 g/cm3
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 59 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: Not applicable
Evaporation rate	: not determined
9.2 Other information	
Solids by weight	: 60,51 %

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020

Volatile organic compounds : 39,48 % (VOC) content

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No dangerous	reaction know	n under	conditions	of	normal use	
---------------------	---	--------------	---------------	---------	------------	----	------------	--

10.4 Conditions to avoid

Conditions to avoid	 Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
---------------------	--

10.5 Incompatible materials

Materials to avoid	:	Keep away from oxidizing agents, strongly alkaline and
		strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products		Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.
Thermal decomposition	:	Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg, Calculation method
Skin corrosion/irritation	:	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Components:

xylene :	
Acute dermal toxicity	: Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity
	point estimate

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish

Remarks: No data is available on the product itself.

12.2 Persistence and degradability

Biodegradability	: No data available
------------------	---------------------

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	:	The product contains dangerous substances for the
information		environment (see chapter no 3).
		The concentration of each substance should be borne in mind
		in assessing the toxicological effects deriving from the
		preparation.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

: The product should not be allowed to enter drains, water

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18	Revision Date 20.12.2017	Print Date 30.03.2020	
	courses or the soil. Disposal together with normal waste disposal required according to local r	•	
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110* 		

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263

14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
ΙΑΤΑ	:	3

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18	Revision Date 20.12.2017	Print Date 30.03.2020
IMDG		
Packing group	: III	
Labels	: 3	
EmS Code	: F - E,S - E	
IATA		
Packing group	: III	
Labels	: 3	
14.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
IATA		
Environmentally hazardous	: no	
14.6 Special precautions for user		
Remarks	: Packagings smaller or equal to 450 l, tra E of marginal 2301.	nsport according to section

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of : Not applicable Substances of Very High Concern for Authorisation (Article 59).

REACH - List of substances : Not applicable subject to authorisation (Annex XIV)

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020

REACH - Restrictions on the : Banned and/or restricted manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

64742-95-6	Hydrocarbons, C9, aromatics
123-86-4	n-butyl acetate

MAL-Code-Number	: 3-3 (1993) 890-m3 air/10 g
Risk classification according to VbF	: Exempt see user defined free text
Water contaminating class (Germany)	: highly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

according to Regulation (EC) No. 830/2015

TB LECHSYS BRILLIANT RED

Version 2.18

Revision Date 20.12.2017

Print Date 30.03.2020