

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : EPODUR MATT  
Product code : L0290172

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels  
Chemical nature : Dual compound colourless clearcoat

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : [safety@lechler.eu](mailto:safety@lechler.eu)  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight  $\leq 700$ )

### Additional Labelling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Liquid solution

**Hazardous components**

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number average molecular weight <= 700)	25068-38-6 500-033-5 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 30 - < 50
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 20 - < 25
4-methylpentan-2-one	108-10-1 203-550-1 01-2119473980-30	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335	>= 5 - < 10
Substances with a workplace exposure limit :			
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6 238-877-9		>= 25 - < 30

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
Seek medical advice.  
Put eye-washer on working place  
Remove contact lenses.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

If swallowed : If accidentally swallowed obtain immediate medical attention.  
Do NOT induce vomiting.  
Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.  
Seek medical advice.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Keep containers and surroundings cool with water spray.

Unsuitable extinguishing media : Do NOT use water jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).  
  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

Advice on protection against : Prevent the creation of flammable or explosive concentrations

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

fire and explosion

of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

### 7.3 Specific end use(s)

: This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	14807-96-6	TWA	2 mg/m <sup>3</sup>		ACGIH
xylenes	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
4-	108-10-1	TWA	20 ppm	2000-06-16	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

methylpentan-2-one			83 mg/m3		
Further information	:	Indicative			
		STEL	50 ppm 208 mg/m3	2000-06-16	2000/39/EC
Further information	:	Indicative			

### DNEL

4-methylpentan-2-one

: End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 14,7 mg/m3

End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Acute systemic effects  
Value: 115,2 mg/m3

End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 4,2 mg/kg bw/day

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term local effects  
Value: 83 mg/m3

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Acute local effects  
Value: 208 mg/m2

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 83 mg/m3

End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Acute systemic effects  
Value: 208 mg/m3

End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 11,8 mg/kg bw/day

## 8.2 Exposure controls

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

### Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141)
- Hand protection : Solvent-resistant gloves (butyl-rubber) recommended.  
For prolonged or repeated contact use protective gloves.  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing.  
Flame retardant antistatic protective clothing.  
Workers should wear antistatic footwear.

### Environmental exposure controls

- General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Odour : solvent-like



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

Flash point	:	> 23 - 55 °C
Ignition temperature	:	not determined
Lower explosion limit	:	No data available
Upper explosion limit	:	No data available
Auto-ignition temperature	:	Not applicable
pH	:	not determined
Freezing point	:	Not applicable
Boiling point	:	not determined
Vapour pressure	:	1,000 hPa at 50 °C
Density	:	1,2735 g/cm <sup>3</sup>
Water solubility	:	not determined
Partition coefficient: n- octanol/water	:	No data available
Solubility in other solvents	:	not determined
Flow time	:	15 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	:	Not applicable
Evaporation rate	:	not determined

### 9.2 Other information

Solids by weight	:	69,64 %
Volatile organic compounds (VOC) content	:	30,35 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : Not applicable

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Acute toxicity (other routes of administration) : Repeated skin contact may lead to irritation and to sensitisation, possible with cross-sensitisation to other epoxys.

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

#### Components:

##### **xylene :**

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxicity to fish :  
Remarks:  
No data is available on the product itself.

#### 12.2 Persistence and degradability

Biodegradability : No data available

#### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

#### 12.4 Mobility in soil

Mobility : No data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

#### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions:150110\*

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : UN 1263

**IMDG** : UN 1263

**IATA** : UN 1263

#### 14.2 Proper shipping name

**ADR** PAINT

**IMDG** PAINT

**IATA** Paint

#### 14.3 Transport hazard class(es)

**ADR** : 3

**IMDG** : 3

**IATA** : 3

#### 14.4 Packing group

##### **ADR**

Packing group : III

Classification Code : F1

Hazard Identification Number : 30

Labels : 3

##### **IMDG**

Packing group : III

Labels : 3

EmS Code : F-E,S-E

##### **IATA**

Packing group : III

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA

Environmentally hazardous : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

64742-95-6	Hydrocarbons, C9, aromatics
------------	-----------------------------

MAL-Code-Number : 4-6 (1993)  
1.803-m3 air/10 g

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## EPODUR MATT

Version 2.22

Revision Date 05.11.2018

Print Date 31.03.2020

---

Risk classification according to VbF : Exempt  
see user defined free text

Water contaminating class (Germany) : water endangering  
VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### 15.2 Chemical safety assessment

No data is available on the product itself.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.