

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EPOFAN PRIMER R-EC
Product code : L0290175

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels
Chemical nature : Dual compound primer (undercoat)

1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA
Via Cecilio 17
22100 Como- CO-
Telephone : +39031586111
Telefax : +39031586206
E-mail address : safety@lechler.eu
Responsible/issuing person

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Hazard pictograms

:



Signal word

: Warning

Hazard statements

: H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 25068-38-6 Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight 700 - 1100)
- 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)

Additional Labelling:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Chemical nature : Liquid pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight 700 - 1100)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 15 - < 17,5
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 10 - < 12,5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 5 - < 10
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (number average molecular weight <= 700)	25068-38-6 500-033-5 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 5 - < 10
zinc oxide	1314-13-2 215-222-5 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=1) (Chronic M=1)	>= 0,25 - < 1
Substances with a workplace exposure limit :			
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 12,5 - < 15
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6 238-877-9		>= 5 - < 10
1-methoxy-2-propanol	107-98-2 203-539-1 01-2119457435-35	Flam. Liq. 3; H226 STOT SE 3; H336	>= 1 - < 5
aluminium orthophosphate	7784-30-7 232-056-9 01-2119971255-34-0006		>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
Do NOT use solvents or thinners.
Put shower on working place
- In case of eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.
Seek medical advice.
Put eye-washer on working place
Remove contact lenses.
- If swallowed : If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
Seek medical advice.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Keep containers and surroundings cool with water spray.
- Unsuitable extinguishing media : Do NOT use water jet.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.
Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ventilate the area.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers.
Clean contaminated surface thoroughly.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Dam up.
Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Use only in area provided with appropriate exhaust ventilation.
Avoid contact with skin, eyes and clothing.
Smoking, eating and drinking should be prohibited in the application area.
Avoid inhalation of vapour or mist.
For personal protection see section 8.
Thoroughly mix before using
After using, store in a well-sealed container
- Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
When transferring from one container to another apply earthing measures and use conductive hose material.
No sparking tools should be used.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
No smoking.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Observe label precautions.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Solvent vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Electrical installations / working materials must comply with the technological safety standards.
Keep away from sources of ignition - No smoking.
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

7.3 Specific end use(s)

: This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
barium sulfate	7727-43-7	TWA	10 mg/m3	2007-01-01	ACGIH
xylenes	1330-20-7	TWA	50 ppm 221 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skin Indicative			
		STEL	100 ppm 442 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skin Indicative			
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	TWA	2 mg/m3		ACGIH
1-methoxypropan-2-ol	107-98-2	TWA	100 ppm 375 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skin Indicative			
		STEL	150 ppm 568 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skin Indicative			
aluminium orthophosphate	7784-30-7	TWA	1 mg/m3	2008-01-01	ACGIH
zinc oxide	1314-13-2	TWA	2 mg/m3	2007-01-01	ACGIH
		STEL	10 mg/m3	2007-01-01	ACGIH

DNEL

trizinc bis(orthophosphate)

: End Use: Workers
Exposure routes: Inhalation
Potential health effects: Local effects
Value: 5 mg/m3

End Use: Workers
Exposure routes: Skin contact
Potential health effects: Local effects

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

		Value: 83 ppm
		End Use: Consumers Exposure routes: Skin contact Potential health effects: Local effects Value: 83 ppm
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Local effects Value: 2,5 mg/m3
		End Use: Consumers Exposure routes: Ingestion Potential health effects: Chronic effects Value: 0,83 ppm
zinc oxide	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Local effects Value: 5 mg/m3
		End Use: Workers Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 83 ppm
		End Use: Consumers Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 83 ppm
		End Use: Consumers Exposure routes: Inhalation Potential health effects: Local effects Value: 2,5 mg/m3
		End Use: Consumers Exposure routes: Ingestion Potential health effects: Chronic effects Exposure time: 8 h Value: 0,83 ppm
barium sulfate	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 10 mg/m3
		End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Value: 10 mg/m³

End Use: Consumer use

Exposure routes: Inhalation

Potential health effects: Long-term systemic effects

Value: 10 mg/m³

End Use: Consumer use

Exposure routes: Ingestion

Potential health effects: Long-term systemic effects

Value: 13000 mg/kg

PNEC

trizinc bis(orthophosphate)

: Fresh water

Value: 0,206 mg/l

Marine water

Value: 0,0061 mg/l

Fresh water sediment

Value: 117,8 mg/kg

Marine sediment

Value: 56,5 mg/kg

Soil

Value: 35,6 mg/kg

zinc oxide

: Fresh water

Value: 0,0206 mg/l

Marine water

Value: 0,0061 mg/l

Fresh water sediment

Value: 117,8 mg/kg

Marine sediment

Value: 56,5 mg/kg

Soil

Value: 35,6 mg/kg

barium sulfate

: Fresh water

Value: 0,115 mg/l

Fresh water sediment

Value: 600,4 mg/kg

Soil

Value: 207,7 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

8.2 Exposure controls

Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.
Respirator with combination filter for vapour/particulate (EN 141)
- Hand protection : Solvent-resistant gloves (butyl-rubber) recommended. For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact. Personnel should wear protective clothing. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.

Environmental exposure controls

- General advice : Try to prevent the material from entering drains or water courses.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
pH	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,6667 g/cm ³
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 65 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: Not applicable
Evaporation rate	: not determined

9.2 Other information

Solids by weight	: 83,56 %
Volatile organic compounds (VOC) content	: 16,43 %

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Thermal decomposition : Not applicable

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Acute toxicity (other routes of administration) : Repeated skin contact may lead to irritation and to sensitisation, possible with cross-sensitisation to other epoxys.

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

Components:

xylene :

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

zinc oxide :

Acute oral toxicity : LD50: 7.950 mg/kg, Mouse

Acute inhalation toxicity : LC50: > 5.700 mg/l, 4 h, Rat,

Acute dermal toxicity : LD50: > 2.000 mg/kg, Rat

barium sulfate :

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg, Converted acute toxicity point estimate

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish :
Remarks:
No data is available on the product itself.

zinc oxide : 1

12.2 Persistence and degradability

Biodegradability : No data available

12.3 Bioaccumulative potential

Bioaccumulation : No data available

12.4 Mobility in soil

Mobility : No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The product should not be allowed to enter drains, water courses or the soil.
Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
The following Waste Codes are only suggestions:150110*

SECTION 14: Transport information

14.1 UN number

- ADR : UN 1263
- IMDG : UN 1263
- IATA : UN 1263

14.2 Proper shipping name

- ADR PAINT
- IMDG PAINT
- IATA Paint

14.3 Transport hazard class(es)

- ADR : 3
- IMDG : 3
- IATA : 3

14.4 Packing group

- ADR
- Packing group : III
- Classification Code : F1

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

Hazard Identification Number : 30

Labels : 3

IMDG

Packing group : III

Labels : 3

EmS Code : F-E,S-E

IATA

Packing group : III

Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA

Environmentally hazardous : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Banned and/or restricted

107-98-2	1-methoxy-2-propanol
	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
71-36-3	butan-1-ol
1589-47-5	2-methoxypropanol

MAL-Code-Number : 5-6 (1993)
3.469-m3 air/10 g

Risk classification according to VbF : Flash point 21 °C to 55 °C, at 15 °C not miscible in water
Specially dangerous flammable liquids

Water contaminating class (Germany) : water endangering
VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

EPOFAN PRIMER R-EC

Version 1.15

Revision Date 05.11.2018

Print Date 31.03.2020

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.