according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	CB LECHSYS RAY ORANGE
Product code	:	L0290625

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	:	Lechler SpA
		Via Cecilio 17
		22100 Como- CO-
Telephone	:	+39031586111
Telefax	:	+39031586206
E-mail address	:	safety@lechler.eu
Responsible/issuing person		

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single exposure, Category 3 H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Warning

:

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date	11.07.2016	Print Date 31.03.2020
Hazard statements	: H226 H336	Flammable liquid and vap May cause drowsiness or	
Precautionary statements	EUH066Repeate cracking. : Prevention:	d exposure may cause skin	dryness or
	P210	Keep away from heat, hot open flames and other ign smoking.	
	P261	Avoid breathing vapours.	
	Response:	252 IF ON SKIN (or boir)	
	P303 + P301 + P	353 IF ON SKIN (or hair): immediately all contamina Rinse skin with water/show	ted clothing.
	P304 + P340 + P	312 IF INHALED: Remov air and keep comfortable a POISON CENTER or do you feel unwell.	for breathing. Call
	P370 + P378	In case of fire: Use dry sa or alcohol-resistant foam t	
	Storage: P403 + P233	Store in a well-ventilated p container tightly closed.	blace. Keep

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Fluid pigmented dispersion

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Substances with a wor	rkplace exposure limit :	· · · · · · · · · · · · · · · · · · ·	
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 50 - < 70

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

Print Date 31.03.2020

2-methoxy-1- methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 5 - < 10
-------------------------------------	---	--------------------	-------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.	
If inhaled	 Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. 	
In case of skin contact	 Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Put shower on working place 	
In case of eye contact	 Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses. 	
If swallowed	 If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. Keep at rest. 	
4.2 Most important symptoms an	nd effects, both acute and delayed	
Symptoms	: No information available.	
Risks	: No information available.	
4.3 Indication of any immediate medical attention and special treatment needed		
Treatment	 The first aid procedure should be established in consultation with the doctor responsible for industrial medicine. Seek medical advice. 	

SECTION 5: Firefighting measures

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
5.1 Extinguishing media		
Suitable extinguishing media	: Use water spray, alcohol-resistant foan carbon dioxide. Keep containers and surroundings coo	-
Unsuitable extinguishing media	: Do NOT use water jet.	
5.2 Special hazards arising from	the substance or mixture	
Specific hazards during firefighting	 As the product contains combustible of will produce dense black smoke contai products of combustion (see section 10 Exposure to decomposition products m health. Cool closed containers exposed to fire Collect contaminated fire extinguishing must not be discharged into drains. Fire residues and contaminated fire ext be disposed of in accordance with local 	ning hazardous)). hay be a hazard to with water spray. water separately. This tinguishing water must
5.3 Advice for firefighters		

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Solvent vapours are heavier than air and may spread along floors. Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ventilate the area.
----------------------	--

6.2 Environmental precautions

Environmental precautions	: Try to prevent the material from entering drains or water
	courses.
	If the product contaminates rivers and lakes or drains inform
	respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

Print Date 31.03.2020

decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).

Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8. Thoroughly mix before using After using, store in a well-sealed container
Advice on protection against fire and explosion	 Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	: Observe label precautions.
areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage.
	Solvent vapours are heavier than air and may spread along
	floors.
	Vapours may form explosive mixtures with air.
	Electrical installations / working materials must comply with the technological safety standards.
	. .

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
Advice on common storage	 Keep away from sources of ignition - No smoking. Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight. Store in accordance with the particular national regulations. Keep away from oxidising agents and strongly acid or alkaline materials. 	
7.3 Specific end use(s)	: This information is not available.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl	123-86-4	TWA	150 ppm		ACGIH
acetate			713 mg/m3		
		STEL	200 ppm		ACGIH
			950 mg/m3		
2-methoxy-1-	108-65-6 TWA		50 ppm	2000-06-16	2000/39/EC
methylethyl			275 mg/m3		
acetate					
Further information	: skin: Identifies the possibility of significant uptake through the skinIndicative				
		STEL	100 ppm	2000-06-16	2000/39/EC
			550 mg/m3		
Further information	: skin: Ident	ifies the poss	ibility of significant upta	ake through the skinIndic	ative

DNEL n-butyl acetate

: End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm

End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3

PNEC n-butyl acetate

: Water

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

Soil Value: 0,093 mg/kg

8.2 Exposure controls

Personal protective equipment	
Respiratory protection :	Apply technical measures to comply with the occupational exposure limits. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time. Respirator with combination filter for vapour/particulate (EN 141).
Hand protection :	Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Wash your hands and put on barrier creams
Eye protection :	Chemical resistant goggles must be worn.
Skin and body protection :	Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.
Environmental exposure controls	
General advice :	Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
Appearance	: liquid	
Odour	: solvent-like	
Flash point	: > 23 - 55 °C	
Ignition temperature	: not determined	
Lower explosion limit	: No data available	
Upper explosion limit	: No data available	
Auto-ignition temperature	: not applicable	
рН	: not determined	
Freezing point	: not applicable	
Boiling point	: not determined	
Vapour pressure	: 1,000 hPa at 50 °C	
Density	: 1,0258 g/cm3	
Water solubility	: not determined	
Partition coefficient: n-	: No data available	
octanol/water Solubility in other solvents	: not determined	
Flow time	: 65 s 6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 34,74 %	
Volatile organic compounds (VOC) content	: 65,25 %	

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
The product is chemically	stable.	
10.3 Possibility of hazardous	reactions	
Hazardous reactions	: No dangerous reaction known under o	conditions of normal use.
10.4 Conditions to avoid		
Conditions to avoid	 Our products were manufactured in constandards to avoid decomposition and defined conditions. Taking the product type into account, the product in its original packaging the it. 	l degrading under the it is advisable to leave
10.5 Incompatible materials		
Materials to avoid	: Keep away from oxidising agents, stro strongly acid materials in order to avo	
10.6 Hazardous decomposition	on products	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox nitrogen (NOx), dense black smoke.	ide (CO), oxides of
Thermal decomposition	: not applicable	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product		
Acute inhalation toxicity	:	Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects., Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness., Inhalation of airborne droplets may cause irritation of the respiratory tract.
Skin corrosion/irritation	:	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

SECTION 12: Ecological information

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
12.1 Toxicity		
Toxicity to fish	: Remarks: No data is available on the product itself.	
12.2 Persistence and degradability		
Biodegradability	: No data available	
12.3 Bioaccumulative potential		
Bioaccumulation	: No data available	
12.4 Mobility in soil		
Mobility	: No data available	

12.5 Results of PBT and vPvB assessment

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT)., This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	:	There is no data available for this product.
information		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110*

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263

14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

IMDG

Packing group	:	III
Labels	:	3
EmS Code	:	F - E,S - E

IATA

Packing group	:	III
Labels	:	3

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14	Revision Date 11.07.2016	Print Date 31.03.2020
14.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
ΙΑΤΑ		
Environmentally hazardous	: no	
14.6 Special precautions for user		
Remarks	: Packagings smaller or equal to 450 l, tran E of marginal 2301.	nsport according to section

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

MAL-Code-Number (DK)	: 3-1 (1993) 1.358-m3 air/10 g
Risk classification according to VbF	: Exempt see user defined free text
Water contaminating class (Germany)	: slightly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical Safety Assessment

No data is available on the product itself.

SECTION 16: Other information

according to Regulation (EC) No. 830/2015

CB LECHSYS RAY ORANGE

Version 2.14

Revision Date 11.07.2016

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.