according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	CB LECHSYS MAGENTA RED
Product code	:	L0290655

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA
	Via Cecilio 17
	22100 Como- CO-
Telephone	: +39031586111
Telefax	: +39031586206
E-mail address	: safety@lechler.eu
Responsible/issuing person	

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Specific target organ toxicity - single exposure, Category 3, Central nervous system H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date	e 16.05.2018	Print Date 31.03.2020
Signal word	: Warning		
Hazard statements	: H226 H336	Flammable liquid and v May cause drowsiness	•
Precautionary statements	EUH066Repea cracking. : Prevention:	ted exposure may cause sk	in dryness or
	P210	Keep away from heat, h open flames and other smoking.	
	P261	Avoid breathing dust/ fu vapours/ spray.	ıme/ gas/ mist/
	Response:		
	•	P353 IF ON SKIN (or ha immediately all contami Rinse skin with water/sl	inated clothing.
	P304 + P340 +	P312 IF INHALED: Rem air and keep comfortab a POISON CENTER/do unwell.	
	P370 + P378	In case of fire: Use dry or alcohol-resistant foar	
	Storage: P403 + P233	Store in a well-ventilate container tightly closed.	• •

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Fluid pigmented dispersion

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Substances with a workplace exposure limit :			
n-butyl acetate	123-86-4	EUH066	>= 50 - < 70

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

Print Date 31.03.2020

	204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	
2-methoxy-1- methylethyl acetate	108-65-6 203-603-9 01-2119475791-29	Flam. Liq. 3; H226	>= 5 - < 10
barium sulfate	7727-43-7 231-784-4 01-2119491274-35		>= 1 - < 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.
If inhaled	 Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious, place in recovery position and seek medical advice.
In case of skin contact	 Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Put shower on working place
In case of eye contact	 Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses.
If swallowed	 If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No information available.
Risks	: No information available.

4.3 Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date 16.05.2018	Print Date 31.03.2020
Treatment	: The first aid procedure should be es with the doctor responsible for indus Seek medical advice.	
SECTION 5: Firefighting meas	ures	
Suitable extinguishing media	: Use water spray, alcohol-resistant for	oam, dry chemical or

		carbon dioxide. Keep containers and surroundings cool with water spray.
Unsuitable extinguishing media	:	Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	 As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

5.3 Advice for firefighters

Special protective equipment	:	Wear self-contained breathing apparatus for firefighting if
for firefighters		necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Solvent vapours are heavier than air and may spread along floors. Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ventilate the area.
----------------------	---	---

6.2 Environmental precautions

Environmental precautions	:	Try to prevent the material from entering drains or water courses.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

4 / 14

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	 Clean with detergents. Avoid solvents. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).
	Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling :	Avoid exceeding the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8. Thoroughly mix before using After using, store in a well-sealed container
Advice on protection against : fire and explosion	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Revision Date 16.05.2018	Print Date 31.03.2020
 Observe label precautions. Containers which are opened must kept upright to prevent leakage. Solvent vapours are heavier than ai floors. Vapours may form explosive mixture Electrical installations / working mat the technological safety standards. Keep away from sources of ignition Store between 5° an 35°C in a dry, from source of heat, ignition and dir Store in accordance with the particular 	r and may spread along es with air. terials must comply with - No smoking. well ventilated place away ect sunlight.
: Keep away from oxidizing agents ar materials.	nd strongly acid or alkaline
: This information is not available.	
	 Observe label precautions. Containers which are opened must kept upright to prevent leakage. Solvent vapours are heavier than ai floors. Vapours may form explosive mixture Electrical installations / working mat the technological safety standards. Keep away from sources of ignition Store between 5° an 35°C in a dry, from source of heat, ignition and dir Store in accordance with the particut Keep away from oxidizing agents ar materials.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	C	AS-No.	Value	Control parameters	Update	Basis
n-butyl acetate	12	23-86-4	TWA	150 ppm 713 mg/m3	2007-01-01	ACGIH
			STEL	200 ppm 950 mg/m3	2007-01-01	ACGIH
2-methoxy-1- methylethyl acetate	10	08-65-6	TWA	50 ppm 275 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identi	fies the possi	bility of significant upta	ake through the skinIndic	ative
			STEL	100 ppm 550 mg/m3	2000-06-16	2000/39/EC
Further information	:	skin: Identi	fies the possi	bility of significant upta	ake through the skinIndic	ative
barium sulfate	7	727-43-7	TWA	10 mg/m3	2007-01-01	ACGIH

DNEL n-butyl acetate

: End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date 16.05.2018	Print Date 31.03.2020
	End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3	
barium sulfate	: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic eff Value: 10 mg/m3	fects
	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic eff Value: 10 mg/m3	fects
	End Use: Consumer use Exposure routes: Inhalation Potential health effects: Long-term systemic eff Value: 10 mg/m3	fects
	End Use: Consumer use Exposure routes: Ingestion Potential health effects: Long-term systemic eff	fects
PNEC		
n-butyl acetate	: Water Value: 0,18 mg/l	
	Soil Value: 0,093 mg/kg	
barium sulfate	: Fresh water Value: 0,115 mg/l	
	Fresh water sediment Value: 600,4 mg/kg	
	Soil Value: 207,7 mg/kg	
8.2 Exposure controls		
Personal protective equipment		
Respiratory protection	 Apply technical measures to comply with the exposure limits. This should be achieved by a good general practically feasible- by the use of a local exh lf the occupational exposure limits cannot b exceptional cases suitable respiratory equip 7 / 14 	extraction and -if haust ventilation. e met, in

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date 16.05.2018	Print Date 31.03.2020
	worn only for a short period of time Respirator with combination filter for 141)	
Hand protection	 Solvent-resistant gloves (butyl-rubb For prolonged or repeated contact Protective gloves complying with E Please observe the instructions reg breakthrough time which are provid gloves. Also take into consideration conditions under which the product danger of cuts, abrasion, and the c If used in solution, or mixed with ot conditions which differ from EN 374 the CE approved gloves. Barrier creams may help to protect they should however not be applied occurred. Skin should be washed after contact Wash your hands and put on barrier 	use protective gloves. N 374. garding permeability and led by the supplier of the in the specific local is used, such as the ontact time. her substances, and under 4, contact the supplier of the exposed areas of skin, d once exposure has
Eye protection	: Chemical resistant goggles must be	e worn.
Skin and body protection	: Skin should be washed after contact Personnel should wear protective of Flame retardant antistatic protective Workers should wear antistatic foot	clothing. e clothing.
Environmental exposure contro	bls	
General advice	 Try to prevent the material from encourses. If the product contaminates rivers a respective authorities. 	-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: Not applicable
	8 / 14

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

Print Date 31.03.2020

рН	: not determined
Freezing point	: Not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 0,9505 g/cm3
Water solubility	: not determined
Partition coefficient: n-	: No data available
octanol/water Solubility in other solvents	: not determined
Flow time	: 65 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: Not applicable
Evaporation rate	: not determined

9.2 Other information

Solids by weight	:	26,07 %
Volatile organic compounds (VOC) content	:	73,92 %

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No dangerous reaction known under conditions of normal use.
---------------------	---

10.4 Conditions to avoid

Conditions to avoid	 Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the
	defined conditions.
	Taking the product type into account, it is advisable to leave
	the product in its original packaging thus avoiding transferring

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date 16.05.2018	Print Date 31.03.2020
	it.	
10.5 Incompatible materials		
Materials to avoid	: Keep away from oxidizing agents, stro strongly acid materials in order to avo	
10.6 Hazardous decomposition p	products	
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox nitrogen (NOx), dense black smoke.	ide (CO), oxides of
Thermal decomposition	: Not applicable	

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product	
Acute inhalation toxicity	: Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects., Such as: mucous membrane irritation respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness., Inhalation of airborne droplets may cause irritation of the respiratory tract.
Skin corrosion/irritation	: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	: The concentration of each substance should be borne in min in assessing the toxicological effects deriving from the preparation.
<u>Components:</u>	
barium sulfate : Acute oral toxicity	: Acute toxicity estimate: 500 mg/kg, Converted acute

SECTION 12: Ecological information

:

12.1 Toxicity

Toxicity to fish

Remarks: No data is available on the product itself.

toxicity point estimate

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

12.2 Persistence and degradability	
Biodegradability	: No data available
12.3 Bioaccumulative potential	
Bioaccumulation	: No data available
12.4 Mobility in soil	
Mobility	: No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	:	There is no data available for this product.
information		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions:150110*

SECTION 14: Transport information

14.1 UN number

ADR	: UN 1263
IMDG	: UN 1263
ΙΑΤΑ	: UN 1263

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

4.2 Proper shipping name ADR IMDG IATA	PAINT PAINT Paint	
IMDG	PAINT	
ΙΑΤΑ	Paint	
4.3 Transport hazard class(es)	
ADR	: 3	
IMDG	: 3	
ΙΑΤΑ	: 3	
4.4 Packing group		
ADR		
Packing group	: 111	
Classification Code	: F1	
Hazard Identification Numbe	r : 30	
Labels	: 3	
IMDG		
Packing group	: 111	
Labels	: 3	
EmS Code	: F - E,S - E	
ΙΑΤΑ		
Packing group	: 111	
Labels	: 3	
4.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
ΙΑΤΑ		

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14	Revision Date 16.05.2018	Print Date 31.03.2020
Environmentally hazardous	: no	
14.6 Special precautions for use	r	
Remarks	: Packagings smaller or equal to 450 l, section E of marginal 2301.	transport according to
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable

REACH - Restrictions on the : Banned and/or restricted manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

123-86-4	n-butyl acetate			
108-65-6	2-methoxy-1-methylethyl acetate			
70657-70-4	2-methoxypropyl acetate			

MAL-Code-Number	:	3-1 (1993) 1.010-m3 air/10 g
Risk classification according to VbF	:	Flash point 21 °C to 55 °C, at 15 °C not miscible in water Specially dangerous flammable liquids
Water contaminating class (Germany)	:	slightly water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

according to Regulation (EC) No. 830/2015

CB LECHSYS MAGENTA RED

Version 2.14

Revision Date 16.05.2018

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment

No data is available on the product itself.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.