according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	CB LECHSYS MICA FINE WHITE
Product code	:	L0290885

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Paints, varnishes and enamels
Chemical nature	:	Mono compound enamel - finish coat

### 1.3 Details of the supplier of the safety data sheet

Company	:	Lechler SpA
		Via Cecilio 17
		22100 Como- CO-
Telephone	:	+39031586111
Telefax	:	+39031586206
E-mail address	:	safety@lechler.eu
Responsible/issuing person		

### 1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only. (8.00-18.00)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Skin irritation, Category 2 Specific target organ toxicity - single exposure, Category 3 H226: Flammable liquid and vapour.H315: Causes skin irritation.H336: May cause drowsiness or dizziness.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 12	3.07.2016	Print Date 31.03.2020
Signal word	: Warning		
Hazard statements	: H226 H315 H336	Flammable liquid and vapou Causes skin irritation. May cause drowsiness or di	
Precautionary statements	: <b>Prevention:</b> P210	Keep away from heat, hot s open flames and other igniti smoking.	
	P261 <b>Response:</b> P303 + P361 + P3	Avoid breathing vapours. 353 IF ON SKIN (or hair): T immediately all contaminate Rinse skin with water/showe	d clothing.
	P304 + P340 + P3	312 IF INHALED: Remove air and keep comfortable for a POISON CENTER or doc you feel unwell.	r breathing. Call
	P362 + P364	Take off contaminated clothin before reuse.	-
	P370 + P378	In case of fire: Use dry sand or alcohol-resistant foam to	

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature

: Liquid pigmented dispersion

### Hazardous components

Chemical Name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION (EC) No	[%]
	Registration number	1272/2008)	
xylene	1330-20-7	Flam. Liq. 3; H226	>= 25 - < 30
	215-535-7	Acute Tox. 4; H332	
	01-2119488216-32	Acute Tox. 4; H312	
		Skin Irrit. 2; H315	

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

Print Date 31.03.2020

Quaternary ammonium compounds, coco alkylethyldimethyl, Et sulfates	68308-64-5 269-662-8	Acute Tox. 4; H302 Skin Corr. 1A; H314 Aquatic Acute 1; H400	>= 0,1 - < 1
Substances with a work	place exposure limit :		
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50
mica	12001-26-2		>= 5 - < 10

For the full text of the H-Statements mentioned in this Section, see Section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	<ul> <li>When symptoms persist or in all cases of doubt seek medical advice.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
If inhaled	<ul> <li>Remove to fresh air.</li> <li>Keep patient warm and at rest.</li> <li>If breathing is irregular or stopped, administer artificial respiration.</li> <li>If unconscious place in recovery position and seek medical advice.</li> </ul>
In case of skin contact	<ul> <li>Take off all contaminated clothing immediately.</li> <li>Wash skin thoroughly with soap and water or use recognized skin cleanser.</li> <li>Do NOT use solvents or thinners.</li> <li>Put shower on working place</li> </ul>
In case of eye contact	<ul> <li>Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.</li> <li>Seek medical advice.</li> <li>Put eye-washer on working place</li> <li>Remove contact lenses.</li> </ul>
If swallowed	<ul> <li>If accidentally swallowed obtain immediate medical attention.</li> <li>Do NOT induce vomiting.</li> <li>Keep at rest.</li> </ul>

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	: No information available.
Risks	: No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 13.07.2016	Print Date 31.03.2020
Treatment	: The first aid procedure should be establis with the doctor responsible for industrial r Seek medical advice.	
SECTION 5: Firefighting meas	sures	
5.1 Extinguishing media		
Suitable extinguishing media	: Use water spray, alcohol-resistant foam, carbon dioxide. Keep containers and surroundings cool w	-
Unsuitable extinguishing media	: Do NOT use water jet.	
5.2 Special hazards arising from t	he substance or mixture	
Specific hazards during firefighting	<ul> <li>As the product contains combustible orga will produce dense black smoke containing products of combustion (see section 10).</li> <li>Exposure to decomposition products may health.</li> <li>Cool closed containers exposed to fire with Collect contaminated fire extinguishing we must not be discharged into design.</li> </ul>	ng hazardous / be a hazard to th water spray.

must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### 5.3 Advice for firefighters

Special protective equipment	:	Wear self-contained breathing apparatus for firefighting if
for firefighters		necessary.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	<ul> <li>Solvent vapours are heavier than air and may spread along floors.</li> <li>Ensure adequate ventilation.</li> <li>Use personal protective equipment.</li> <li>Evacuate personnel to safe areas.</li> <li>Keep people away from and upwind of spill/leak.</li> <li>Ventilate the area.</li> </ul>
----------------------	--

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

Print Date 31.03.2020

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up :	<ul> <li>Clean with detergents. Avoid solvents. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).</li> </ul>
	Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and dispose of as hazardous waste.

### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling :	<ul> <li>Avoid exceeding of the given occupational exposure limits (see section 8).</li> <li>Use only in area provided with appropriate exhaust ventilation.</li> <li>Avoid contact with skin, eyes and clothing.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Avoid inhalation of vapour or mist.</li> <li>For personal protection see section 8.</li> <li>Thoroughly mix before using</li> <li>After using, store in a well-sealed container</li> </ul>
Advice on protection against : fire and explosion	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 13.07.2016	Print Date 31.03.2020
Requirements for storage areas and containers	<ul> <li>Observe label precautions. Containers which are opened must be kept upright to prevent leakage. Solvent vapours are heavier than air floors.</li> <li>Vapours may form explosive mixture Electrical installations / working mate the technological safety standards. Keep away from sources of ignition - Store between 5° an 35°C in a dry, w from source of heat, ignition and dire Store in accordance with the particul</li> </ul>	and may spread along s with air. erials must comply with - No smoking. vell ventilated place away ect sunlight.
Advice on common storage	: Keep away from oxidising agents an materials.	d strongly acid or alkaline
7.3 Specific end use(s)		
	: This information is not available.	

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
n-butyl	123-86-4	TWA	150 ppm		ACGIH
acetate			713 mg/m3		
		STEL	200 ppm		ACGIH
			950 mg/m3		
xylenes	1330-20-7	TWA	50 ppm	2000-06-16	2000/39/EC
			221 mg/m3		
Further information	: skin: Identi	fies the poss	ibility of significant upt	ake through the skinInc	licative
		STEL	100 ppm	2000-06-16	2000/39/EC
			442 mg/m3		
Further information	: skin: Identi	fies the poss	ibility of significant upta	ake through the skinInc	licative
mica	12001-26-	TWA			ACGIH
	2		3 mg/m3		

DNEL n-butyl acetate

 End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 13.07.2016	Print Date 31.03.2020
	End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3	
PNEC	: Water	
n-butyl acetate	Value: 0,18 mg/l	
	Soil Value: 0,093 mg/kg	
8.2 Exposure controls		
Personal protective equipme	nt	
Respiratory protection	<ul> <li>Apply technical measures to comply with exposure limits.</li> <li>This should be achieved by a good general practically feasible- by the use of a local If the occupational exposure limits cannon cases suitable respiratory equipment shou short period of time.</li> <li>Respirator with combination filter for variable</li> </ul>	al extraction and -if exhaust ventilation. of be met, in exceptional ald be worn only for a
Hand protection	<ul> <li>Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use pro Protective gloves complying with EN 374 Please observe the instructions regarding breakthrough time which are provided by gloves. Also take into consideration the s under which the product is used, such as abrasion, and the contact time. If used in solution, or mixed with other su conditions which differ from EN 374, con CE approved gloves. Barrier creams may help to protect the ex- should however not be applied once expon Skin should be washed after contact. Wash your hands and put on barrier cream</li> </ul>	4. permeability and v the supplier of the specific local conditions the danger of cuts, ubstances, and under ntact the supplier of the sposed areas of skin, they osure has occurred.
Eye protection	: Chemical resistant goggles must be worn	l.
Skin and body protection	: Skin should be washed after contact. Working clothes must not consist of texti dangerous melting behaviour in case of fi Personnel should wear protective clothing Workers should wear antistatic footwear.	ire. g.

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

version 2.12	Version	2.12	
--------------	---------	------	--

Revision Date 13.07.2016

General advice : Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: > 23 - 55 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: not applicable
рН	: not determined
Freezing point	: not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 1,0352 g/cm3
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 60 s 6 mm Method: ISO/DIN 2431 '84
Relative vapour density	: not applicable
Evaporation rate	: not determined
9.2 Other information	
Solids by weight	: 29,72 %
Volatile organic compounds	: 70,27 %
	8 / 13

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

(VOC) content

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

### 10.4 Conditions to avoid

Conditions to avoid	<ul> <li>Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.</li> <li>Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.</li> </ul>
---------------------	--

### 10.5 Incompatible materials

Materials to avoid	: Keep away from oxidising agents, strongly alkaline and
	strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.
Thermal decomposition	:	not applicable

## **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

### **Product**

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg, Calculation method
Skin corrosion/irritation	:	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

Print Date 31.03.2020

<u>Components:</u> xylene :	
Acute dermal toxicity	: Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Toxicity to fish : Remarks: No data is available on the product itself.

### 12.2 Persistence and degradability

Biodegradability	: No data available
------------------	---------------------

#### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

#### 12.4 Mobility in soil

Mobility : No data available

#### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological	:	There is no data available for this product.
information		

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	: The product should not be allowed to enter drains, water courses or the soil.
	Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 13.07.2016	Print Date 31.03.2020
Contaminated packaging	: Empty containers should be taken thandling site for recycling or disposed According to the European Waste Care not product specific, but applica The Waste code should be assigned the user, the producer and the wast The following Waste Codes are only	al. Catalogue, Waste Codes tion specific. d in discussion between re disposal company.

# **SECTION 14: Transport information**

### 14.1 UN number

ADR	:	UN 1263
IMDG	:	UN 1263
ΙΑΤΑ	:	UN 1263

### 14.2 Proper shipping name

ADR	PAINT
IMDG	PAINT
ІАТА	Paint

## 14.3 Transport hazard class(es)

ADR	:	3
IMDG	:	3
IATA	:	3

### 14.4 Packing group

### ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3

### IMDG

Packing group : I	Π
-------------------	---

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12	Revision Date 13.07.2016	Print Date 31.03.2020
Labels	: 3	
EmS Code	: F - E,S - E	
IATA		
Packing group	: III	
Labels	: 3	
14.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	
IMDG		
Marine pollutant	: no	
IATA		
Environmentally hazardous	: no	
<b>14.6 Special precautions for user</b> Remarks	: Packagings smaller or equal to 450 l, trans E of marginal 2301.	sport according to section

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

: not applicable
: not applicable
: Banned and/or restricted

according to Regulation (EC) No. 830/2015

# **CB LECHSYS MICA FINE WHITE**

Version 2.12

Revision Date 13.07.2016

Print Date 31.03.2020

dangerous substances, preparations and articles (Annex XVII)

123-86-4	n-butyl acetate	
71-36-3	butan-1-ol	

MAL-Code-Number (DK)	:	4-3 (1993) 1.941-m3 air/10 g
Risk classification according to VbF	:	Flash point 21 °C to 55 °C, at 15 °C not miscible in water Specially dangerous flammable liquids
Water contaminating class (Germany)	:	water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

#### **15.2** Chemical Safety Assessment

No data is available on the product itself.

### **SECTION 16: Other information**

#### Full text of H-Statements referred to under sections 2 and 3.

Repeated exposure may cause skin dryness or cracking.
Flammable liquid and vapour.
Harmful if swallowed.
Harmful in contact with skin.
Causes severe skin burns and eye damage.
Causes skin irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.
Very toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.