according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

Revision Date 01.09.2015

Print Date 31.03.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	CB LECHSYS WHITE PEARL EXTRA BRIGHT
Product code	:	L0290888

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the	: Paints, varnishes and enamels
Substance/Mixture	
Chemical nature	: Coloured concentrated base

1.3 Details of the supplier of the safety data sheet

Company	: Lechler SpA	
	Via Cecilio 17	
	22100 Como-	CO-
Telephone	: +39031586111	
Telefax	: +39031586206	i
E-mail address	: safety@lechler	.eu
Responsible/issuing person		

1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)

This telephone number is available during office hours only. (8.00-18.00)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Skin irritation, Category 2 Specific target organ toxicity - single exposure, Category 3

H226: Flammable liquid and vapour. H315: Causes skin irritation. H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Warning :

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date	01.09.2015	Print Date 31.03.2020
Hazard statements	: H226 H315 H336	Flammable liquid and va Causes skin irritation. May cause drowsiness o	
Precautionary statements	: Prevention: P210	Keep away from heat, ho open flames and other ig smoking.	
	P261 Response:	Avoid breathing vapours.	
	P303 + P361 +	P353 IF ON SKIN (or hair immediately all contamin Rinse skin with water/sho	ated clothing.
	P304 + P340 +	P312 IF INHALED: Remo air and keep comfortable a POISON CENTER or o you feel unwell.	ve person to fresh for breathing. Call
	P362 + P364	Take off contaminated clobefore reuse.	othing and wash it
	P370 + P378	In case of fire: Use dry s or alcohol-resistant foam	-

Hazardous components which must be listed on the label:

• 123-86-4 n-butyl acetate

2.3 Other hazards

None known. No hazards resulting from the material as supplied. The information required is contained in this Material Safety Data Sheet.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Fluid pigmented dispersion

Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 25 - < 30
Quaternary ammonium compounds, coco	68308-64-5 269-662-8	Acute Tox. 4; H302 Skin Corr. 1A; H314	>= 0,1 - < 1

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

4.2

Revision Date 01.09.2015

Print Date 31.03.2020

alkylethyldimethyl, Et sulfates		Aquatic Acute 1; H400	
Substances with a w	orkplace exposure limit :		
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	EUH066 Flam. Liq. 3; H226 STOT SE 3; H336	>= 30 - < 50
mica	12001-26-2		>= 12,5 - < 15

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.	
If inhaled	 Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. 	
In case of skin contact	 Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Put shower on working place 	
In case of eye contact	 Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. Seek medical advice. Put eye-washer on working place Remove contact lenses. 	
If swallowed	: If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. Keep at rest.	
Most important symptoms and eff	ects, both acute and delayed	
Symptoms	: No information available.	

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	: The first aid procedure should be established in consultation
	with the doctor responsible for industrial medicine.
	Seek medical advice.

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

Revision Date 01.09.2015

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
Unsuitable extinguishing media	:	Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	 As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health.
	Cool closed containers exposed to fire with water spray. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Aduing for fination to a	

5.3 Advice for firefighters

Special protective equipment	:	Wear self-contained breathing apparatus for firefighting if
for firefighters		necessary.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Solvent vapours are heavier than air and may spread along floors. Ensure adequate ventilation. Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ventilate the area.
----------------------	--

6.2 Environmental precautions

Environmental precautions	: Try to prevent the mater	ial from entering drains or water
	courses.	
	If the product contamina	ites rivers and lakes or drains inform
	respective authorities.	

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up		:	Clean with detergents. Avoid solvents.
-------------------------	--	---	--

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

Revision Date 01.09.2015

Print Date 31.03.2020

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Dam up. Soak up with inert absorbent material and dispose of as hazardous waste.

6.4 Reference to other sections

Refer to section 15 for specific national regulation.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding of the given occupational exposure limits (see section 8). Use only in area provided with appropriate exhaust ventilation. Avoid contact with skin, eyes and clothing. Smoking, eating and drinking should be prohibited in the application area. Avoid inhalation of vapour or mist. For personal protection see section 8. Thoroughly mix before using After using, store in a well-sealed container
Advice on protection against fire and explosion	 Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. When transferring from one container to another apply earthing measures and use conductive hose material. No sparking tools should be used. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	: Observe label precautions.
areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage.
	Solvent vapours are heavier than air and may spread along
	floors.
	Vapours may form explosive mixtures with air.
	Electrical installations / working materials must comply with
	the technological safety standards.
	Keep away from sources of ignition - No smoking.
	Store between 5° an 35°C in a dry, well ventilated place away
	from source of heat, ignition and direct sunlight.

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020
	Store in accordance with the particula	ar national regulations.
Advice on common storage	: Keep away from oxidising agents and materials.	l strongly acid or alkaline
7.3 Specific end use(s)		
	: This information is not available.	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value	Control parameters Update		Basis
n-butyl	123-86-4	TWA	150 ppm		ACGIH
acetate			713 mg/m3		
		STEL	200 ppm		ACGIH
			950 mg/m3		
xylenes	1330-20-7	TWA	50 ppm	2000-06-16	2000/39/EC
			221 mg/m3		
Further information	: skin: Iden	dentifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm	2000-06-16	2000/39/EC
			442 mg/m3		
Further information	: skin: Iden	: Identifies the possibility of significant uptake through the skinIndicative			
mica	12001-26-	TWA			ACGIH
	2		3 mg/m3		

DNEL n-butyl acetate

: End Use: Professional use Exposure routes: Skin contact Potential health effects: Local effects Exposure time: 8 h Value: 7 ppm

End Use: Professional use Exposure routes: Inhalation Potential health effects: Local effects Value: 48 mg/m3

PNEC n-butyl acetate

: Water Value: 0,18 mg/l

> Soil Value: 0,093 mg/kg

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

Revision Date 01.09.2015

8.2 Exposure controls

Personal protective equipment	
Respiratory protection :	Apply technical measures to comply with the occupational exposure limits. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time. Respirator with combination filter for vapour/particulate (EN 141).
Hand protection :	Solvent-resistant gloves (butyl-rubber) For prolonged or repeated contact use protective gloves. Protective gloves complying with EN 374. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Wash your hands and put on barrier creams
Eye protection :	Chemical resistant goggles must be worn.
Skin and body protection :	Skin should be washed after contact. Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire. Personnel should wear protective clothing. Workers should wear antistatic footwear.
Environmental exposure controls	
General advice :	Try to prevent the material from entering drains or water courses. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020
Flash point	: > 23 - 55 °C	
Ignition temperature	: not determined	
Lower explosion limit	: No data available	
Upper explosion limit	: No data available	
Auto-ignition temperature	: not applicable	
рН	: not determined	
Freezing point	: not applicable	
Boiling point	: not determined	
Vapour pressure	: 1,0 hPa at 50 °C	
Density	: 1,0261 g/cm3	
Water solubility	: not determined	
Partition coefficient: n-	: No data available	
octanol/water Solubility in other solvents	: not determined	
Flow time	: 100 s 6 mm Method: ISO/DIN 2431 '84	
Relative vapour density	: not applicable	
Evaporation rate	: not determined	
9.2 Other information		
Solids by weight	: 29,72 %	
Volatile organic compounds (VOC) content	: 70,27 %	

SECTION 10: Stability and reactivity

10.1 Reactivity

None reasonably foreseeable.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions

: No dangerous reaction known under conditions of normal use.

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

CD LECHIJIS WITTE TEARL EATRA DRIUTT				
Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020		
10.4 Conditions to avoid				
Conditions to avoid	 Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it. 			
10.5 Incompatible materials				
Materials to avoid	: Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.			
10.6 Hazardous decomposition	products			
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monox nitrogen (NOx), dense black smoke.	kide (CO), oxides of		
Thermal decomposition	: not applicable			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Product

Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2.000 mg/kg, Calculation method
Skin corrosion/irritation	:	Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.
Further information	:	The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.
<u>Components:</u> xylene :		
	:	Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

SECTION 12: Ecological information

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020
Toxicity to fish	: Remarks: No data is available on the product itself.	
12.2 Persistence and degradabili	ty	
Biodegradability	: No data available	
12.3 Bioaccumulative potential		
Bioaccumulation	: No data available	
12.4 Mobility in soil		
Mobility	: No data available	
12.5 Results of PBT and vPvB as	ssessment	

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological	:	There is no data available for this product.
information		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.
Contaminated packaging	 Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110*

SECTION 14: Transport information

14.1 UN number

ADR :	UN 1263
-------	---------

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020
IMDG	: UN 1263	
ΙΑΤΑ	: UN 1263	
14.2 Proper shipping name		
ADR	PAINT	
IMDG	PAINT	
ΙΑΤΑ	Paint	
14.3 Transport hazard class(es)		
ADR	: 3	
IMDG	: 3	
IATA	: 3	
14.4 Packing group		
ADR		
Packing group	: III	
Classification Code	: F1	
Hazard Identification Number	: 33	
Labels	: 3	
IMDG		
Packing group	: III	
Labels	: 3	
EmS Code	: F-E,S-E	
IATA		
Packing group	: III	
Labels	: 3	
14.5 Environmental hazards		
ADR		
Environmentally hazardous	: no	

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4	Revision Date 01.09.2015	Print Date 31.03.2020
IMDG		
Marine pollutant	: no	
ΙΑΤΑ		
Environmentally hazardous	: no	
14.6 Special precautions for user		
Remarks	 Packages smaller than or equal to 450 litres, not goods/merchandise of Class 3 Packages smaller than or equal to 30 litres, not go f Class 3 	

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	not applicable
MAL-Code-Number (DK)	:	4-3 (1993) 1.924-m3 air/10 g
Risk classification according to VbF	:	Flash point 21 °C to 55 °C, at 15 °C not miscible in water Specially dangerous flammable liquids
Water contaminating class (Germany)	:	water endangering VWVWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

15.2 Chemical Safety Assessment

No data is available on the product itself.

according to Regulation (EC) No. 830/2015

CB LECHSYS WHITE PEARL EXTRA BRIGHT

Version 1.4

Revision Date 01.09.2015

Print Date 31.03.2020

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

Repeated exposure may cause skin dryness or cracking.
Flammable liquid and vapour.
Harmful if swallowed.
Harmful in contact with skin.
Causes severe skin burns and eye damage.
Causes skin irritation.
Harmful if inhaled.
May cause drowsiness or dizziness.
Very toxic to aquatic life.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.