

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : CB LECHSYS COARSE LENS SILVER  
Product code : L0290896

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Paints, varnishes and enamels  
Substance/Mixture  
Chemical nature : Coloured concentrated base

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : [safety@lechler.eu](mailto:safety@lechler.eu)  
Responsible/issuing person

#### 1.4 Emergency telephone number

Tel. +39-031-586301 - This telephone number is available during office hours only. (8.00-18.00)
---

This telephone number is available during office hours only.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

Hazard pictograms

:



Signal word

: Warning

Hazard statements

:

H226  
H315  
H336  
H412

Flammable liquid and vapour.  
Causes skin irritation.  
May cause drowsiness or dizziness.  
Harmful to aquatic life with long lasting effects.

Precautionary statements

:

**Prevention:**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273

Avoid release to the environment.

P280

Wear protective gloves/ eye protection/ face protection.

**Response:**

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 123-86-4 n-butyl acetate

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature

: Fluid pigmented dispersion

#### Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No	Concentration [%]
---------------	-------------------	---------------------------------------	----------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

	Registration number	1272/2008)	
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Note C	>= 30 - < 50
Hydrocarbons, C9, aromatics	64742-95-6 918-668-5 01-2119455851-35-0006	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066 Note P	>= 1 - < 2,5
Quaternary ammonium compounds, C12-14 (even-numbered)- alkylethyldimethyl, ethyl sulphates	939-607-9 01-2119977130-42	Acute Tox. 4; H302 Acute Tox. 3; H311 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 (Acute M=10) (Chronic M=10)	>= 0,1 - < 0,25
Substances with a workplace exposure limit :			
n-butyl acetate	123-86-4 204-658-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25 - < 30
aluminium powder (stabilised)	7429-90-5 231-072-3 01-2119529243-45	Flam. Sol. 1; H228 Note T	>= 10 - < 12,5

For the full text of the H-Statements mentioned in this Section, see Section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
Put shower on working place

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

- 
- |                        |   |
|------------------------|---|
| In case of eye contact | : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.<br>Seek medical advice.<br>Put eye-washer on working place<br>Remove contact lenses. |
| If swallowed           | : If accidentally swallowed obtain immediate medical attention.<br>Do NOT induce vomiting.<br>Keep at rest.   |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |                             |
|----------|-----------------------------|
| Symptoms | : No information available. |
| Risks    | : No information available. |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |  |
|-----------|--|
| Treatment | : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.<br>Seek medical advice. |
|-----------|--|

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.<br>Keep containers and surroundings cool with water spray. |
| Unsuitable extinguishing media | : Do NOT use water jet.   |

### 5.2 Special hazards arising from the substance or mixture

- |                                      |   |
|--------------------------------------|---|
| Specific hazards during firefighting | : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).<br>Exposure to decomposition products may be a hazard to health.<br>Cool closed containers exposed to fire with water spray.<br>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
|--------------------------------------|---|

### 5.3 Advice for firefighters

- |   |  |
|---|--|
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |
|---|--|

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

#### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container. The contaminated area should be cleaned up immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises water (45 parts by volume)/ethanol or isopropanol (50 parts)/concentrated (d: 0.880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts)/water (95 parts).  
  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

#### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° and 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

German storage class : 3 Flammable liquids

### 7.3 Specific end use(s)

: This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
xylenes	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm	2000-06-16	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

			442 mg/m3		
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
n-butyl acetate	123-86-4	TWA	50 ppm	2016-03-01	ACGIH
		STEL	150 ppm	2016-03-01	ACGIH
aluminium (Stabilized powder)	7429-90-5	TWA	1 mg/m3	2013-03-01	ACGIH
Further information	:	Aluminium			

### DNEL

n-butyl acetate

: End Use: Professional use  
Exposure routes: Skin contact  
Potential health effects: Local effects  
Exposure time: 8 h  
Value: 7 ppm

End Use: Professional use  
Exposure routes: Inhalation  
Potential health effects: Local effects  
Value: 48 mg/m3

### PNEC

n-butyl acetate

: Water  
Value: 0,18 mg/l

Soil  
Value: 0,093 mg/kg

## 8.2 Exposure controls

### Personal protective equipment

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141)

Hand protection : Solvent-resistant gloves (butyl-rubber) recommended.  
For prolonged or repeated contact use protective gloves.  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams

Eye protection : Chemical resistant goggles must be worn.

Skin and body protection : Skin should be washed after contact.  
Personnel should wear protective clothing.  
Flame retardant antistatic protective clothing.  
Workers should wear antistatic footwear.

### Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid  
Odour : solvent-like  
Flash point : > 23 - 55 °C  
Ignition temperature : not determined  
Lower explosion limit : No data available  
Upper explosion limit : No data available  
Auto-ignition temperature : Not applicable  
pH : not determined  
Freezing point : Not applicable  
Boiling point : not determined  
Vapour pressure : 1,000 hPa



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

at 50 °C

Density	: 0,9651 g/cm <sup>3</sup>
Water solubility	: not determined
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 70 s 4 mm Method: ASTM D 1200 '82
Relative vapour density	: Not applicable
Evaporation rate	: not determined

### 9.2 Other information

Solids by weight	: 22,89 %
Volatile organic compounds (VOC) content	: 77,1 %

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

None reasonably foreseeable.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	: No dangerous reaction known under conditions of normal use.
---------------------	---

### 10.4 Conditions to avoid

Conditions to avoid	: Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions. Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.
---------------------	--

### 10.5 Incompatible materials

Materials to avoid	: Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
--------------------	--

### 10.6 Hazardous decomposition products

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : Not applicable

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

##### Components:

##### **xylene :**

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

##### **Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates :**

Acute oral toxicity : LD50: > 570 mg/kg, Rat, OECD Test Guideline 401

Acute dermal toxicity : LD50: 528 mg/kg, Rabbit, OECD Test Guideline 402

### SECTION 12: Ecological information

#### 12.1 Toxicity

Toxicity to fish :  
Remarks:  
No data is available on the product itself.

Toxicity to fish  
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl : LC50: 13,8 mg/l  
Exposure time: 96 h  
Species: Danio rerio (zebra fish)

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

---

sulphates	Method: OECD Test Guideline 203
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	: 10
Toxicity to fish (Chronic toxicity)	
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	: 0,032 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	Exposure time: 35 d
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	Species: Pimephales promelas (fathead minnow)
	Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	
Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	: NOEC: 0,0007 mg/l
	Exposure time: 21 d
	Species: Daphnia magna (Water flea)
	Method: OECD Test Guideline 211

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3).  
The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Disposal together with normal waste is not allowed. Special

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.  
The following Waste Codes are only suggestions:150110\*

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

#### 14.2 Proper shipping name

ADR PAINT  
IMDG PAINT  
IATA Paint

#### 14.3 Transport hazard class(es)

ADR : 3  
IMDG : 3  
IATA : 3

#### 14.4 Packing group

ADR  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

IMDG

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

---

Packing group : III  
Labels : 3  
EmS Code : F - E, S - E

### IATA

Packing group : III  
Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA

Environmentally hazardous : no

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles : Banned and/or restricted

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

(Annex XVII)

	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
64742-95-6	Hydrocarbons, C9, aromatics
71-36-3	butan-1-ol

MAL-Code-Number : 5-3 (1993)  
4.758-m3 air/10 g

German storage class : 3: Flammable liquids  
(TRGS 510)

Risk classification according to VbF : Flash point 21 °C to 55 °C, at 15 °C not miscible in water  
Specially dangerous flammable liquids

Water contaminating class (Germany) : water endangering  
VWWWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

### 15.2 Chemical safety assessment

No data is available on the product itself.

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3.

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## CB LECHSYS COARSE LENS SILVER

Version 2.14

Revision Date 20.12.2018

Print Date 31.03.2020

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.