


## TEXTURE ADDITIVES LECHSYS



1000 g +  
100 - 200 g

### DESCRIPTION

Texture additives of synthetic nature mixable with some enamels of Lechsys and Lechsys Effect system to obtain finishes with textured look. They are available in 3 different grain sizes according to the effect you wish to obtain:

- 29502 LECHSYS FINE TEXTURE (20 micron)**
- 29503 LECHSYS MEDIUM TEXTURE (50 micron)**
- 29504 LECHSYS MAGNUM TEXTURE (100 micron)**

In the Lechler MAP® software, "manufacture" TEXTURE, you can find all ARCHITECTURAL colours you can obtain with these effects.

### USE

These additives are used to bestow a texture and non-slip aesthetical effect to enamels used to paint industrial manufactured items in general, sports equipment, door and window frames and fixtures, lighting, furniture components, industrial machinery, street and extra-urban furniture.

### CHARACTERISTICS

The enamels obtained after adding these additives ensure:

- Excellent scratch resistance and a high non-slip effect
- Uniform grainy aspect
- Constant gloss (lower than the colour with no Texture additive)
- High resistance to chemicals and detergents

### SUBSTRATE PREPARATION

Refer to the TDS of the enamels in which these additives are mixed.

### APPLICATION

#### Mixing ratio:

	<b>weight</b>
Virtual LECHSYS enamels LS532-533 (derived from binders 29532-29533) <b>or</b>	1000 g
Virtual LECHSYS EFFECT enamel LS534 (derived from binder 29534)	
TEXTURE ADDITIVES 29502 - 29503 - 29504	100-200 g



We suggest adding the additive after preparing the enamel, mix with electric stirrer until complete dispersion, then add hardener and thinner according to the mixing ratio indicated in the TDS of the reference enamels.

The use of these additives can affect the enamel opacity according to the colours.

Therefore, in case of light and low covering colours envisage the application of one more coat, respecting flash-off times of enamels.

---

#### **DRYING TIME**

Refer to the TDS of the enamels in which these additives are mixed.

---

#### **NOTE**

The final look of the textured film is dependent on the application conditions.

**TECHNICAL DATA SHEET N° 0722-GB**  
**UPDATED 12/2018**

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.