




00915 - SANDER ABRASIVE PASTE



Ready for use



By pad or Scotch Brite

DESCRIPTION

Special water based compound with matting action containing special selected micronized abrasives.

USE

In car refinishing for matting the surfaces to retouch, above all in fade-out touch-ups. It allows a perfect adhesion of the two-pack topcoats (lacquers and clears) to original or old films.

CHARACTERISTICS

- Easy to apply
- Easy elimination of residual traces by simply washing with water without leaving any marks
- Good flattening action
- It does not scratch the original films
- High coverage
- Water based product (VOC = 0)
- Silicone free
- Easy to use by practical tube package

SUBSTRATE PREPARATION

Clean with water.

APPLICATION

Set out the necessary quantity of the product on a cotton-wool pad or on Scotch Brite UF and rub lengthwise to reach the complete matting.

Clean with sponge soaked in water, then degrease with 00695 SILICONE REMOVER SLOW or 00699 HYDROCLEANER / 00665 HYDROCLEANER SLOW.

OVERCOATINGS

- MACROFAN TOPCOATS
- HYDROFAN
- MACROFAN UHS CLEARCOATS and HYDROFAN CLEARCOAT

TECHNICAL DATA SHEET N° 0393-GB UPDATED 09/2011

All information contained in this data sheet is the result of carefully controlled tests and is correct to the best of Lechler's knowledge at the time of issue. Since conditions of use are beyond the control of the manufacturer, information contained herein is without warranty, implied or otherwise, and final determination of the suitability of any information or material for the use contemplated and the manner of use is the sole responsibility of the user. FOR PROFESSIONAL USE ONLY.