

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Marston Universaldichtung
Article number: MMD

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Sealing material
Adhesive

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Marston Domsel GmbH
Bergheimer Str. 15
53909 Zülpich / GERMANY
Phone +49 (0) 22 52 94 15 0
Fax +49 (0) 22 52 17 44
Homepage www.marston-domsel.de
E-mail info@marston-domsel.de

Address enquiries to

Technical information info@marston-domsel.de

Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +49 (0)89-19240 (24h) (English)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Flam. Liq. 2: H225 Highly flammable liquid and vapour.
Eye Irrit. 2: H319 Causes serious eye irritation.
STOT SE 3: H336 May cause drowsiness or dizziness.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms



Signal word

DANGER

Contains:

Ethyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice / attention.
P312 Call a POISON CENTER / doctor /.../ if you feel unwell.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/national regulation.

Special labelling

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Human health dangers

Has a degreasing effect on the skin.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

Range [%]	Substance
20 - < 40	Ethyl acetate CAS: 141-78-6, EINECS/ELINCS: 205-500-4, EU-INDEX: 607-022-00-5, Reg-No.: 01-2119475103-46-XXXX GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336
1 - < 15	Acetone CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8 GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Change soaked clothing.

Inhalation

Ensure supply of fresh air.
In the event of symptoms seek medical treatment.

Skin contact

When in contact with the skin, clean with soap and water.
Consult a doctor if skin irritation persists.

Eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion

Get medical advice.
Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam.
Dry powder.
Water spray jet.
Carbon dioxide.

Extinguishing media that must not be used

Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
Carbon monoxide (CO).

5.3 Advice for firefighters

Use self-contained breathing apparatus.
Wear full protective suit.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, sawdust, universal absorbent, diatomaceous earth).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Provide good room ventilation even at ground level (vapours are heavier than air).
Use solvent-resistant equipment.
Avoid spilling or spraying in enclosed areas.
Keep away from all sources of ignition - Refrain from smoking.
Ignitable mixtures can be formed in the empty container.
Take precautionary measures against static discharges.
Use explosion-proofed equipment/fittings and non-sparking tools.
Ground/bond container and receiving equipment.
Do not eat, drink, smoke or take drugs at work.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Only use containers that are approved specifically for the substance/product.
Provide solvent-resistant and impermeable floor.
Do not store together with oxidizing agents.
Protect from heat/overheating.
Keep in a cool place, heat causes increase in pressure and risk of bursting.
Keep container in a well-ventilated place.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Ethyl acetate
CAS: 141-78-6, EINECS/ELINCS: 205-500-4, EU-INDEX: 607-022-00-5, Reg-No.: 01-2119475103-46-XXXX
Long-term exposure: 200 ppm, 730 mg/m ³
Short-term exposure (15-minute): 400 ppm, 1460 mg/m ³
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8
Long-term exposure: 500 ppm, 1210 mg/m ³
Short-term exposure (15-minute): 1500 ppm, 3620 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Ethyl acetate
CAS: 141-78-6, EINECS/ELINCS: 205-500-4, EU-INDEX: 607-022-00-5, Reg-No.: 01-2119475103-46-XXXX
Eight hours: 200 ppm, 734 mg/m ³
Short-term (15-minute): 400 ppm, 1468 mg/m ³
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8
Eight hours: 500 ppm, 1210 mg/m ³

DNEL

Substance
Ethyl acetate, CAS: 141-78-6
Industrial, inhalative, Acute - local effects: 1468 mg/m ³ .
Industrial, inhalative, Acute - systemic effects: 1468 mg/m ³ .
Industrial, inhalative, Long-term - local effects: 734 mg/m ³ .
Industrial, inhalative, Long-term - systemic effects: 734 mg/m ³ .
Industrial, dermal, Long-term - systemic effects: 63 mg/kg bw/d.
general population, dermal, Long-term - systemic effects: 37 mg/kg bw/d.
general population, oral, Long-term - systemic effects: 4,5 mg/kg bw/d.
general population, inhalative, Long-term - systemic effects: 367 mg/m ³ .
general population, inhalative, Long-term - local effects: 367 mg/m ³ .
general population, inhalative, Acute - systemic effects: 734 mg/m ³ .
general population, inhalative, Acute - local effects: 734 mg/m ³ .

PNEC

Substance
Ethyl acetate, CAS: 141-78-6
oral (food), 200 mg/kg.
sewage treatment plants (STP), 650 mg/l.
soil, 0,24 mg/kg dw.
sediment (seawater), 0,125 mg/kg.
sediment (freshwater), 1,25 mg/kg.
seawater, 0,026 mg/l.
freshwater, 0,26 mg/l.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. In full contact: (0,7 mm) Butyl rubber, >480 min (EN 374-1/-2/-3). In splash contact: (0,6 mm) Butyl rubber, >120 min (EN 374-1/-2/-3).
Skin protection	Solvent-resistant protective clothing (EN 340)
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols.
Respiratory protection	Respiratory protection mask in the event of high concentrations. Short term: filter apparatus, filter A. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	red
Odor	like acetone
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	> 35
Flash point [°C]	ca. -5
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	No information available.
Upper explosion limit	No information available.
Oxidising properties	not applicable
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	No information available.
Bulk density [kg/m³]	not applicable
Solubility in water	partially miscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	No information available.
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	No information available.
Decomposition temperature [°C]	No information available.

9.2 Other information

none

SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Reactions with oxidizing agents.

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.

10.4 Conditions to avoid

See SECTION 7

Strong heating.

10.5 Incompatible materials

See SECTION 7

Strong oxidizing agent.

strong acids

Amines

Strong basic compounds

10.6 Hazardous decomposition products

Flammable gases/vapours.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
ATE-mix, dermal, > 2000 mg/kg bw.
ATE-mix, oral, > 2000 mg/kg bw.
Substance
Acetone, CAS: 67-64-1
LD50, dermal, Rabbit: 20000 mg/kg (IUCLID).
LD50, oral, Rat: 5800 mg/kg (IUCLID).
LC50, inhalative, Rat: 76 mg/l (4h) (IUCLID).
Ethyl acetate, CAS: 141-78-6
LD50, dermal, Rabbit: > 18000 mg/kg.
LD50, oral, Rat: 5620 mg/kg.
LC50, inhalative, Rat: 5,86 mg/l 4 h (Lit.).

Serious eye damage/irritation	Toxicological data of complete product are not available. Irritant Calculation method
Skin corrosion/irritation	Toxicological data of complete product are not available. No classification. Calculation method
Respiratory or skin sensitisation	Toxicological data of complete product are not available. No classification. Calculation method
Specific target organ toxicity — single exposure	Toxicological data of complete product are not available. Vapours may cause drowsiness and dizziness. Calculation method
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Frequent persistent contact with the skin can cause skin irritation. Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Acetone, CAS: 67-64-1
LC50, (96h), Oncorhynchus mykiss: 5540 mg/l (Lit.).
EC50, (48h), Daphnia magna: 6100 mg/l (Lit.).
Ethyl acetate, CAS: 141-78-6
LC50, (96h), Pimephales promelas: 230 mg/l (IUCLID).
EC50, (48h), Daphnia magna: 717 mg/l (IUCLID).
EC50, (48h), Desmodesmus subspicatus: 3300 mg/l (IUCLID).
EC10, (16h), Pseudomonas putida: 2900 mg/l (IUCLID).

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not applicable
Biological degradability	not applicable

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

Ecological data of complete product are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.

Waste no. (recommended)

080409*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID 1133

Inland navigation (ADN) 1133

Marine transport in accordance with IMDG 1133

Air transport in accordance with IATA 1133

14.2 UN proper shipping name

Transport by land according to
ADR/RID

Adhesives

- Classification Code

F1

- Label



- ADR LQ

5 I

- ADR 1.1.3.6 (8.6)

Transport category (tunnel restriction code) 2 (D/E)

Inland navigation (ADN)

Adhesives

- Classification Code

F1

- Label



Marine transport in accordance with
IMDG

Adhesives

- EMS

F-E, S-D

- Label



- IMDG LQ

5 I

Air transport in accordance with IATA Adhesives

- Label



14.3 Transport hazard class(es)

Transport by land according to
ADR/RID

3

Inland navigation (ADN)

3

Marine transport in accordance with
IMDG

3

Air transport in accordance with IATA

3

14.4 Packing group

Transport by land according to
ADR/RID

II

Inland navigation (ADN)

II

Marine transport in accordance with
IMDG

II

Air transport in accordance with IATA

II

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for young people. Observe employment restrictions for mothers-to-be and nursing mothers.
- VOC (2010/75/CE)	ca. 36%

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H336 May cause drowsiness or dizziness.
H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
ATE = acute toxicity estimate
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging
DMEL = Derived Minimum Effect Level
DNEL = Derived No Effect Level
EC50 = Median effective concentration
ECB = European Chemicals Bureau
EEC = European Economic Community
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified Chemical Substances
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50 = Inhibition concentration, 50%
IMDG = International Maritime Code for Dangerous Goods
IUCLID = International Uniform Chemical Information Database
LC50 = Lethal concentration, 50%
LD50 = Median lethal dose
LC0 = lethal concentration, 0%
LOAEL = lowest-observed-adverse-effect level
MARPOL = International Convention for the Prevention of Marine Pollution from Ships
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
PBT = Persistent, Bioaccumulative and Toxic substance
PNEC = Predicted No-Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
STP = Sewage Treatment Plant
TLV®/TWA = Threshold limit value – time-weighted average
TLV®STEL = Threshold limit value – short-time exposure limit
VOC = Volatile Organic Compounds
vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Customs Tariff

not determined

Classification procedure

Flam. Liq. 2: H225 Highly flammable liquid and vapour. (On basis of test data)
Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)
STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)

Modified position

none

Copyright: Chemiebüro®