Printing date 11.10.2017 Revision: 11.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

F Formulation or re-packing

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC14 Metal surface treatment products
- · Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- · Article category AC7 Metal articles
- · Application of the substance / the mixture

Testing material for nondestructive surface crack detection

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MR® Chemie GmbH

Nordstr. 61-63

59427 Unna (Germany)

Tel. +49 (0)2303 95151 0

Fax: +49 (0)2303 95151 10

post@mr-chemie.de

www.mr-chemie.de

· Further information obtainable from:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

1.4 Emergency telephone number:

24h- Emergency Contact Phone Number

For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident

Call Day or Night within USA and Canada: 1 800 424 9300 Outside USA and Canada: 001 703 527 3887

In-Country Emergency Number for:

Germany: 0800-181-7059

China: 4001 204937 (Mandarin)
Hong Kong: 800 968 793 (Cantonese)
India: 000 800 100 7141 (Hindi)
South Africa: 0 800 983 611 (English)

(WISAG FMO Cargo Service GmbH & CO.KG)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
	isoparaffinic hydrocarbons	50-60%
	Asp. Tox. 1, H304	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-XXXX	propane Flam. Gas 1, H220 Press. Gas (Comp.). H280	25-30%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-XXXX	butane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1, H220	25-30%

- · Propellant: Propane-Butane
- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Take affected persons into fresh air and keep quiet.

Seek medical treatment in case of complaints.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Not relevant - aerosol can.

· 4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness

Unconsciousness

Nausea

- · Information for doctor: With aspiration danger of the pulmonary edema and/or pneumonia.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, e.g. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

(Contd. on page 4)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 3)

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:				
106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))				
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)			
AGW (Germany)	Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG			
74-98-6 propane				
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG			

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Filter AX-P2

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.

· Protection of hands:

For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.

Check the permeability prior to each anewed use of the glove.

· Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level \leq 6 Supplier for suitable protection gloves:

ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - http://www.arbeitssicherheitdortmund.de

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing

GB

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 4)

9.1 Information on basic physical and	chemical properties
General Information	Fro Postado
Appearance:	
Form:	Aerosol
Colour:	Black
Odour: Odour threshold:	Characteristic Not determined.
pH-value:	Not determined.
·	Not determined.
Change in condition	He determine and
Melting point/freezing point: Initial boiling point and boiling range	Undetermined.
	• • • • • • • • • • • • • • • • • • • •
Flash point:	-97 °C
	Basis: propellant
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Not determined - aerosol.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0,5 Vol %
Upper:	10,9 Vol %
Vapour pressure at 20 °C:	8300 hPa
•	Basis: propellant
Spray can internal pressure (20 °C):	4.8 bar
Spray can internal pressure (50 °C):	7.0 bar
Density at 20 °C:	0,83 g/cm³
	Basis: active substance
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	99,7 %
VOC (EU)	99 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 5)

· 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

Avoid open flame or electrical ignition.

Danger of bursting of the aerosol can during overheating

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Strong oxidizing agents.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))

Inhalative LC50/4 h 658 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Low, no classification
- · Serious eye damage/irritation low, no classification.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability

Moderately /partly biodegradable

Halbwertzeit in der Umwelt < 10 Tage

- · 12.3 Bioaccumulative potential May be accumulated in organism
- · 12.4 Mobility in soil No further relevant information available.
- Other information: At longer term no harmful effects for water organisms are expected.
- · Additional ecological information:
- · General notes: Water hazard class 1: weakly water-endangering
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Eliminate the pure, unchanged substance in accordance with local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 6)

· Waste disposal key:

For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.

The indications for Waste key reflect the pure unmodified product and are only a recommendation.

· European waste catalogue		
07 07 04*	other organic solvents, washing liquids and mother liquors	
15 01 10*	packaging containing residues of or contaminated by dangerous substances	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS floromobile
1412 Transport beyond class(cs)	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1 Gases.
Class Label	2.1 2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	Na
Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
-	SW22 For AEROSOLS with a maximum capa
	of 1 litre: Category A. For AEROSOLS wit
	capacity above 1 litre: Category B. For WAS AEROSOLS: Category C, Clear of living quarter
Segregation Code	SG69 For AEROSOLS with a maximum capacit
	1 litre: Segregation as for class 9. Stow "separa from" class 1 except for division 1.4.

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

	(Contd. of page 7
	Segregation as for the appropriate subdivision o class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to	Annex II
of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
. , ,	Not permitted as Excepted Quantity
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- · Waterhazard class:

Water hazard class 1: slightly hazardous for water.(In accordance with classification VwVwS,appendix 4)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The data in this safety data sheet are based on our knowledge at the time of the revision. The information should give you reference points for a safe handling of the product specified in this safety data sheet. The data are not transferable to other products. If the product specified in this safety data sheet is mixed or processed with other materials, the data cannot be transferred without examination.

Relevant phrases

The wording of the listed risk phrases are those of the individual raw materials.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

· Recommended restriction of use

Existing national and local laws concerning chemicals are to be considered.

Department issuing SDS:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38

(Contd. on page 9)

Printing date 11.10.2017 Revision: 11.10.2017

Trade name: MR® 76 S Magnetic powder suspension, black

Aerosol

(Contd. of page 8)

· Contact:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

- GB