Printing date 26.03.2018 Revision: 26.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MR® 85 Remover

Aerosol

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

F Formulation or re-packing

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC14 Metal surface treatment products

PC9a Coatings and paints, thinners, paint removers

PC35 Washing and cleaning products (including solvent based products)

· Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- Article category AC7 Metal articles
- · Application of the substance / the mixture

Testing material for nondestructive surface crack detection

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MR® Chemie GmbH

Nordstr. 61-63

59427 Unna (Germany) Tel. +49 (0)2303 95151 0 Fax: +49 (0)2303 95151 10 post@mr-chemie.de www.mr-chemie.de

· Further information obtainable from:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

1.4 Emergency telephone number:

24h- Emergency Contact Phone Number For Chemical Emergency, Spill, Leak, Fire, Exposure or

Accident (WISAG FMO Cargo Service GmbH & CO.KG)
Call Day or Night within USA and Canada: 1 800 424 9300
Outside USA and Canada: 001 703 527 3887

In-Country Emergency Number for: Germany: 0800-181-7059

China: 4001 204937 (Mandarin)
Hong Kong: 800 968 793 (Cantonese)
India: 000 800 100 7141 (Hindi)
South Africa: 0 800 983 611 (English)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The mixture is classified according to Regulation (EC) No 1272/2008 according to the most recent ATP.



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 1)



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

2-Propanol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-63-0	2-Propanol	60 - 70%
EINECS: 200-661-7	Flam. Liq. 2, H225	
Reg.nr.: 01-2119457558-25-XXXX	Eye Irrit. 2, H319; STOT SE 3, H336	
	butane (containing ≤ 0,1 % butadiene (203-450-8))	20 - 30%
EINECS: 203-448-7	Flam. Gas 1, H220	
Reg.nr.: 01-2119474691-32-XXXX	1 /2	nd an name (1)

(Contd. on page 3)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

CAS: 74-98-6 propane 10 - 20% EINECS: 200-827-9 Flam. Gas 1, H220 Press. Gas (Comp.), H280

· Propellant: Propane-Butane

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

Seek medical advice if symptoms occurs or in cases of doubt.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Not relevant aerosol can.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

Information for doctor:

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, e.g. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · Recommended storage temperature: 5 45 °C, 41 113 °F
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with lin	· Ingredients with limit values that require monitoring at the workplace:		
67-63-0 2-Propanol	67-63-0 2-Propanol		
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm		
AGW (Germany)	Long-term value: 500 mg/m³, 200 ppm 2(II);DFG, Y		
74-98-6 propane			
AGW (Germany)	Long-term value: 1800 mg/m³, 1000 ppm 4(II);DFG		
106-97-8 butane (co	ontaining ≤ 0,1 % butadiene (203-450-8))		
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		
AGW (Germany)	Long-term value: 2400 mg/m³, 1000 ppm 4(II);DFG		
123-86-4 n-Butylace	etat		
WEL (Great Britain)	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm		
AGW (Germany)	Long-term value: 300 mg/m³, 62 ppm 2(I);AGS, Y		
· DNELs	· DNELs		
67-63-0 2-Propanol			
Dermal Long-tern	Dermal Long-term - systemic effects, worker 888 mg/kg bw/day (worker)		
Inhalative Long-tern	Inhalative Long-term - systemic effects, worker 500 mg/m³ (worker)		

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 4)

· PNECs	
67-63-0 2-Propanol	
Aquatic compartment, freshwater	140.9 mg/L (freshwater)
Aquatic compartment - marine water	140.9 mg/L (marine water)
Aquatic compartment- sediment in freshwater	552 mg/kg sed dw (sediment fresh water)
Aquatic compartment sediment in marine water	552 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	28 mg/kg dw (soil)
Sewage treatment plant	2,251 mg/L (sewage treatment plant)
Oral secondary poisoning	160 mg/kg food (food secundary poisoning)

· Ingredients with biological limit values:

67-63-0 2-Propanol

BGW (Germany)

25 mg/l

Untersuchungsmaterial: Vollblut

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

25 mg/l

Untersuchungsmaterial: Urin

Probennahmezeitpunkt: Expositionsende bzw. Schichtende

Parameter: Aceton

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX-P2

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.

· Protection of hands:

Check the permeability prior to each anewed use of the glove.

For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 6

Supplier for suitable protection gloves:

ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - http://www.arbeitssicherheitdortmund.de

(Contd. on page 6)

Revision: 26.03.2018 Printing date 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 5)

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses • Body protection: Protective work clothing

• 9.1 Information on basic physical and chemical properties General Information Appearance: Form: Colour: Clear Odour: Codour: Characteristic Not determined. PH-value: Not determined. Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: Flammability (solid, gas): Not applicable, Initial boiling point and boiling range: Not determined. Flammability (solid, gas): Not applicable, Initial boiling point and boiling range: Product is not explosive. However, formation explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % Upper: 1.2 Vol % Vapour pressure at 20 °C: Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Not determined. Not determined. Not determined. Not determined. Pendity to yellow bushance Relative density Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined.		cal properties
Appearance: Form: Colour: Colour: Codour: Codour: Characteristic Not determined. PH-value: Not determined. Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Pecomposition temperature: Not determined - aerosol. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Lower: Lower: 1.5 Vol % Upper: 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Solubility in / Miscibility with water: Not determined. Not applicable. Partition coefficient: n-octanol/water: Not determined.		chemical properties
Colour: Odour threshold: Not determined. PH-value: Not determined. Change in condition Melting point and boiling range: Not applicable, as aerosol. Flash point: Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined. Product is not selfigniting. Explosion limits: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: 1.5 Vol % Upper: 1.5 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): 5.0 bar Spray can internal pressure (50 °C): 8.5 bar Density at 20 °C: 0.786 g/cm³ Basis: active substance Relative density Not determined. Not applicable. Partition coefficient: n-octanol/water: Not determined.	· Appearance:	
Odour: Odour threshold: Odour threshold: Not determined. PH-value: Not determined. Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: Flammability (solid, gas): Not applicable, Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined - aerosol. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 nPa Basis: propellant Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Relative density Not determined. Not determined. Not determined. Not determined. Not determined. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Not determined.	Form:	Aerosol
Odour threshold: Not determined. pH-value: Not determined. Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: -80 ℃ Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. - Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: 1.5 Vol % Upper: 12 Vol % Vapour pressure at 20 ℃: 8,300 hPa Basis: propellant Spray can internal pressure (20 ℃): 5.0 bar Spray can internal pressure (50 ℃): 8.5 bar Density at 20 ℃: 0.786 g/cm³ Basis: active substance Relative density Not determined. Vapour density Not determined. Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Not determined.		
PH-value: Not determined. Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. - Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive properties: Explosion limits: Lower: Upper: 1.5 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Relative density Not determined. Not determined. Not determined. Not applicable. Partition coefficient: n-octanol/water: Not determined. Not determined. Viscosity: Dynamic: Kinematic: Not determined.		
Change in condition Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: -80 °C Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Relative density Vapour density Vapour density Not determined. Not determined. Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.		
Melting point/freezing point: Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: -80 ℃ Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 ℃: Spray can internal pressure (20 ℃): Spray can internal pressure (20 ℃): Spray can internal pressure (50 ℃): Spray can internal p	<u>'</u>	Not determined.
Initial boiling point and boiling range: Not applicable, as aerosol. Flash point: -80 °C Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Relative density Not determined. Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.		Hadan was d
Flash point: -80 °C Basis: propellant Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): 5.0 bar Spray can internal pressure (50 °C): 8.5 bar Density at 20 °C: Relative density Vapour density Vapour density Vapour density Not determined. Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined.		
Flammability (solid, gas): Not applicable. Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Density at 20 °C: Relative density Vapour density Vapour density Vapour density Vapour density Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.		
Flammability (solid, gas): Ignition temperature: Not determined - aerosol. Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % Vapour pressure at 20 ℃: 8,300 hPa Basis: propellant Spray can internal pressure (20 ℃): Spray can internal pressure (50 ℃): Density at 20 ℃: Relative density Vapour density Vapour density Vapour density Not determined. Not applicable. Not miscible or difficult to mix. Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.	· Flash point:	
• Ignition temperature: • Decomposition temperature: • Auto-ignition temperature: • Explosive properties: • Explosion limits: Lower: Upper: • Vapour pressure at 20 °C: • Spray can internal pressure (20 °C): • Spray can internal pressure (50 °C): • Relative density • Vapour density • Vapour density • Solubility in / Miscibility with water: • Partition coefficient: n-octanol/water • Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.		· ·
Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 ℃: Spray can internal pressure (20 ℃): Spray can internal pressure (50 ℃): Spray can internal pressure (50 ℃): Density at 20 ℃: Relative density Vapour density Vapour density Vapour density Vapour density Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Not determined.	, , , , , , , , , , , , , , , , , , ,	• • • • • • • • • • • • • • • • • • • •
Auto-ignition temperature: Product is not selfigniting. Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % Vapour pressure at 20 °C: Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Density at 20 °C: Relative density Vapour density Vapour density Vapour density Vapour density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. Not determined. Not determined.	· · · · · · · · · · · · · · · · · · ·	Not determined - aerosol.
Explosive properties: Product is not explosive. However, formation explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Spray can internal pressure (50 °C): Density at 20 °C: Relative density Vapour density Vapour density Vapour density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. Not determined. Not determined.	· Decomposition temperature:	Not determined.
explosive air/vapour mixtures are possible. Explosion limits: Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant 5.0 bar Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): Density at 20 °C: 0.786 g/cm³ Basis: active substance Relative density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Not determined.	· Auto-ignition temperature:	Product is not selfigniting.
Lower: Upper: 1.5 Vol % 12 Vol % Vapour pressure at 20 °C: 8,300 hPa Basis: propellant 5.0 bar Spray can internal pressure (20 °C): 5.0 bar Spray can internal pressure (50 °C): Density at 20 °C: Relative density Vapour density Vapour density Vapour density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined.	· Explosive properties:	Product is not explosive. However, formation explosive air/vapour mixtures are possible.
Upper: 12 Vol % · Vapour pressure at 20 °C: 8,300 hPa Basis: propellant · Spray can internal pressure (20 °C): 5.0 bar · Spray can internal pressure (50 °C): 8.5 bar · Density at 20 °C: 0.786 g/cm³ Basis: active substance · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not applicable. · Solubility in / Miscibility with water: Not determined. · Partition coefficient: n-octanol/water: Not determined. · Viscosity: Not determined. Kinematic: Not determined. Kinematic: Not determined. Organic solvents: 100.0 %	· Explosion limits:	
· Vapour pressure at 20 °C: Spray can internal pressure (20 °C): Spray can internal pressure (50 °C): O.786 g/cm³ Basis: active substance Not determined. Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. Not determined.		
Basis: propellant Spray can internal pressure (20 °C): 5.0 bar Spray can internal pressure (50 °C): 8.5 bar Density at 20 °C: 0.786 g/cm³ Basis: active substance Relative density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Not determined. Viscosity: Not determined. Kinematic: Not determined.	Upper:	12 Vol %
 Spray can internal pressure (20 °C): 5.0 bar Spray can internal pressure (50 °C): 8.5 bar Density at 20 °C: 0.786 g/cm³ Basis: active substance Relative density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Not determined. Not determined. Not determined. Kinematic: Not determined. Not determined. Organic solvents: 100.0 % 	· Vapour pressure at 20 °C:	8,300 hPa
 Spray can internal pressure (50 °C): 8.5 bar Density at 20 °C: 0.786 g/cm³ Basis: active substance Relative density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Not determined. Viscosity: Not determined. Kinematic: Not determined. Organic solvents: 100.0 % 	•	
 Density at 20 °C: Basis: active substance Relative density Not determined. Vapour density Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic:		
Relative density Vapour density Vapour density Evaporation rate Not determined. Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. Not determined. Not determined.	· Spray can internal pressure (50 °C):	8.5 bar
 Relative density Vapour density Evaporation rate Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. 100.0 % 	· Density at 20 °C:	
 Vapour density Evaporation rate Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. Not determined. 100.0 % 		
 Evaporation rate Not applicable. Solubility in / Miscibility with water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Not determined. Kinematic: Not determined. Organic solvents: 100.0 % 		
· Solubility in / Miscibility with water: · Partition coefficient: n-octanol/water: · Viscosity: Dynamic: Kinematic: Organic solvents: Not miscible or difficult to mix. Not determined. Not determined. Not determined. 100.0 %	•	
water: Not miscible or difficult to mix. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic: Not determined. Kinematic: Not determined. Organic solvents: 100.0 %	<u>'</u>	Not applicable.
· Partition coefficient: n-octanol/water: Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. Organic solvents: 100.0 %		Nich orthograph and dreep the second
 Viscosity: Dynamic: Kinematic: Organic solvents: Not determined. Not determined. 100.0 % 		
Dynamic:Not determined.Kinematic:Not determined.Organic solvents:100.0 %	· Partition coefficient: n-octanol/water:	Not determined.
Kinematic: Not determined. Organic solvents: 100.0 %		
Organic solvents: 100.0 %		
VOC (EU) 100 %		
	VOC (EU)	100 %

(Contd. on page 7)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Danger of bursting of the aerosol can during overheating

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
67-63-0 2-	67-63-0 2-Propanol		
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rbt)	
Inhalative	LC50/4 h	30 mg/l (rat)	
106-97-8	106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))		
Inhalative	LC50/4 h	658 mg/l (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1: weakly water-endangering
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 7)

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Eliminate the pure, unchanged substance in accordance with local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste disposal key:

For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.

The indications for Waste key reflect the pure unmodified product and are only a recommendation.

· European	waste catalogue
14 06 03*	other solvents and solvent mixtures
15 01 10*	packaging containing residues of or contaminated by dangerous substances

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

14.1 UN-Number	
	LINIOFO
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.

(Contd. on page 9)

Printing date 26.03.2018 Revision: 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 8) · Danger code (Kemler): F-D.S-U · EMS Number: · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of Segregation Code 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1L Code: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity Transport category

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E0

Not permitted as Excepted Quantity

• UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

D

· Directive 2012/18/EU

Tunnel restriction code

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:
- · Waterhazard class:

Water hazard class 1: slightly hazardous for water.(In accordance with classification VwVwS,appendix 4)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The data in this safety data sheet are based on our knowledge at the time of the revision. The information should give you reference points for a safe handling of the product specified in this safety data sheet. The data are not transferable to other products. If the product specified in this safety data sheet is mixed or processed with other materials, the data cannot be transferred without examination.

(Contd. on page 10)

Revision: 26.03.2018 Printing date 26.03.2018

Trade name: MR® 85 Remover

Aerosol

(Contd. of page 9)

· Relevant phrases

The wording of the listed risk phrases are those of the individual raw materials.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eve irritation.

H336 May cause drowsiness or dizziness.

· Recommended restriction of use

Existing national and local laws concerning chemicals are to be considered.

Department issuing SDS:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38

Contact:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.